

UNSUPPORTED WITH A PVC COATING

A thin, lightweight glove with a second skin feel, which is ideal for industries where cleanliness is a priority. The flexible PVC coating provides chemical resistance and good grip.

FEATURES

- > Ultra-thin, light glove with a second skin feel
- Seals and protects the hand against chemicals while remaining flexible
- Impermeable for working in damp or greasy environments
- > Lint-free, dust-free
- Fully coated with a scalloped edge and embossed finish
- > Non-powdered, 'slip-on' treatment
- > Seamless liner prevents irritation
- > Surface enables a secure grip on slippery objects
- > Designed for easy movement and continuous wear
- > Extended bonded sleeve to protect the full arm
- > Ergonomic Fit
- > Thickness: 0.3mm







SUITABLE FOR

Typical Industries

- Agriculture
- Electronics
- Healthcare
- Petrochemical
- Pharmaceutical

Suitable Applications

- Cleaning
- General Purpose
- Handling Pesticides
- Laboratories

CAT III EN 388:2016 EN ISO 3741:2016/Type C 2777 2000X See overleaf for explanation





B0710

PRODUCT INFORMATION

MATERIALS	LINER:	Unsupported, unlined	
	COATING:	PVC	
COLOUR	White		
LENGTH (mm)	600		
CUFF STYLE	Gauntlet		

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL	SHOB7101 SHOB7102 SHOB7103 SHOB7104	10 pairs per bag 100 pairs per case

RECOMMENDATIONS FOR USE

PROTECTION AGAINST


MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

- USE: Light chemical resistant glove. Not suitable for thermal, electrical, cut and high chemicals handling. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS







*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
В	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	0	25% Ammonium hydroxide
G	Diethylamine	P	30% Hydrogen peroxide
Н	Tetrahydrofurane	S	40% Hydrofluoric acid
I	Ethyl acetate	T	37% Formaldehyde

GLOVES	BREAKTHROUGH TIME
Α	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical

8

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-B0710_0620_1