RILEY

STREAM EVO

Frameless metal-free wraparound safety eyewear

The Riley Stream Evo is a lightweight safety spectacle with a secure fit, adjustable nose bridge, and flexible temple tips. Metal-free for electrical safety, it's slim for comfort with ear defenders and includes a microfiber pouch, making it perfect for manufacturing and construction.

- TWILIGHT
- CLEAR
- BRONZE/BROWN
- GREEN WELDING 3
- GREEN
- GREY
- YELLOW
- BLUE
- GREEN WELDING 5
- INDOOR/OUTDOOR


Clear



Clear


Grey


LED

ADJUSTABLE NOSE BRIDGE

DIELECTRIC

SOFT TPE

SPORTS STYLE

TEMPFLEX

ULTRA LIGHTWEIGHT

FEATURES

- Single wraparound polycarbonate lens
- Soft, adjustable, anti-slip nose bridge
- Flexible temple tips
- Co-injected bi-colour thermoplastic rubber temples provide a secure fit
- Slim temples enhance comfort when worn with ear defenders
- 100% metal free
- Supplied with a microfibre storage pouch
- Weight: 23g
- 9.5-Base lens

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary. Published date: 16/11/2026

GLOBUS

RILEY | STREAM EVO

LENS TYPE	REF	LENS MARKING	FRAME MARKING	PROTECTS AGAINST	COATINGS
GREEN WELDING 5	RLY00376	5 1 F K N CE / Z87+ W3	REN166 FT CE UKCA Z87+	Impacts,UV Radiation,Infrared	TECTON 400
GREEN	RLY00374	4 1 F K N CE W4		Impacts,UV Radiation,Infrared	
TWILIGHT	RLY00364	5-1.7 1 FT CE U6 L1.7 / I 1	REN166 FT CE UKCA Z87+ AS/NZS 1337.1 Lic. SMK40933	Impacts,UV Radiation	ARIDA 400
INDOOR/OUTDOOR	RLY00377	5-1.7 1 FT CE / Z87+ U6 L1.7		Impacts,UV Radiation	
BLUE	RLY00363	2C-1.2 1 FT CE U6 / IO 0		Impacts,UV Radiation	ARIDA 400, Moisture Repellent, UV400
GREY	RLY00362	5-2.5 1 FT K N CE U6 L2.5 / I 2		Impacts,UV Radiation,Solar Radiation	TECTON 400
CLEAR	RLY00361	2C-1.2 1 FT K N CE U6 / IO 0		Impacts,UV Radiation	
YELLOW	RLY00371	2-1.2 1 FT K N CE U6 / I 0		Impacts,UV Radiation	
BRONZE/BROWN	RLY00369	2C-1.4 1 FT K N CE U6 L1.3 / I 1		Impacts,UV Radiation	
BLUE	RLY00365	2C-1.4 1 FT K N CE U6 S / I 1		Impacts,UV Radiation	
GREEN WELDING 3	RLY00375	3 1 F K N CE / Z87+ W3 / I 3		Impacts,UV Radiation,Infrared	
TWILIGHT	RLY00360	5-1.7 1 FT / Z87+ U6 L1.7	RFT CE	Impacts,UV Radiation	Anti-Fog

GENERAL SPECIFICATION

WEIGHT	23g

COMPONENT SPECIFICATION

COMPONENT	MATERIAL
LENS	Polycarbonate
NOSE BRIDGE	Thermoplastic Elastomers (TPE)
TEMPLE	Thermoplastic TR90, Thermoplastic Elastomers (TPE)
HINGE	Thermoplastic TR90

PACKAGING

PER BOX	10
PER CASE	200

ADDITIONAL INFORMATION

CERTIFICATION LEGEND

or click here

DECLARATION OF CONFORMITY

or click here

VIEW PRODUCT ONLINE

or click here

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary. Published date: 16/11/2026

GLOBUS