

Butyl II 874

Superior resistance to highly corrosive acids

Ideal for those working with biohazards and specifically when handling ketones, amines and esters. The Butyl rubber provides the highest permeation resistance to toxic gases and water vapours.

Features

- ▲ Impermeable for working in damp or greasy environments
- ▲ Protection against ketones, alcohols, nerve agents
- ▲ Provides the highest permeation resistance to gases and water vapors of any protective material used to make gloves
- ▲ Unlined to reduce risk of lint contamination
- ▲ Smooth finish
- ▲ Length: 35cm
- ▲ Thickness: 0.35mm
- ▲ Rolled cuff

Certifications

CAT III	EN 374-1: 2016/ Type B	EN 388:2016 + A1:2018	EN 374-5: 2016	EN 388: 2016
				
A, B, C, I, K, L, M, N, P, S, T	2110X	Micro Organisms + Virus	0010X	

Suitable industries & applications

Industries

- ▲ Manufacturing
- ▲ Chemicals

- ▲ Utilities

Applications

- ▲ Acetones and Ketones
- ▲ Acids
- ▲ Painting and Finishing
- ▲ Chemical Handling and Containment
- ▲ Labouring



Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

salesusa@globusgroup.com
+1 83 337 54747

Butyl II 874

Superior resistance to highly corrosive acids

Product information

Materials	Liner:	Unlined/Unsupported
	Coating:	Butyl
Colour	Black	
Length	390mm	
Cuff Style	Gauntlet	

Ordering information

7/S	BST8741	Items per Case 12 x Pairs
8/M	BST8742	
9/L	BST8743	
10/XL	BST8744	
11/XXL	BST8745	

Additional information

Certification legend




or click [here](#)

Declaration of conformity



or click [here](#)

View product online



or click [here](#)

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

salesusa@globusgroup.com
+1 83 337 54747