

sноша. **542X**

UNCOATED, CUT LEVEL A GLOVE

A flexible, light glove which provides light protection against cuts, abrasion and rips

FEATURES

- > Cut resistance: Level A (EN 388:2016)
- > Uncoated, high performance polyethylene (HPPE)
- > Level 4 (maximum) resistance for tears
- > Great freedom of movement for the wrist
- > Optimal dexterity and tactile feel retained
- > No irritation by seams in contact with the skin
- > Standard finish without special treatment
- > Minimal irritation risks
- > Elasticated cuff



COMPATIBLE

SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- ConstructionElectronics Manufacturing
- Machinery
- Steel and Metals

Suitable Applications

- Assembling Metal Parts
- Delicate Operation
- Finishing
- Glass Repair
- Inspection
- Stamping

CERTIFICATION





2240A



See overleaf for explanation



showa. 542X

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE	
	COATING:	Uncoated	
COLOUR	White		
LENGTH (mm)	250 (size dependent)		
CUFF STYLE	Elasticated knit wrist		

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/S 7/M 8/L 9/XL	SHO542X1 SHO542X2 SHO542X3 SHO542X4	10 pairs per bag 200 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with light cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-5 0-4 0-4 A-F P I I I Impact Resistance Straight Blade Cut Resistance (EN ISO: 13997) Puncture Resistance Tear Resistance Circular Blade Cut Resistance

Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- **T:** +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- **T:** +971 4 882 9962
- **F:** +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2020 Globus (Shetland) Ltd | SHO-DATA-542X_0620_1

EU compliance certificate delivered by the notified body SGS Fimko Oy, Särkiniementie 3, Helsinki, 00211, Finland (Notified Body number 0598)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.