

Tsunami Grip® Lightweight, Seamless, New Foam Technology Palm Coated, rPET Recycled Gloves with Cut, Abrasion, and Puncture Resistance

Description

These general-purpose gloves have a 15-gauge gray-and-black seamless rPET/nylon/spandex shell. Recycled polyester (rPET) fiber utilizes reprocessed PET plastic bottles as an environmentally conscious method to help reduce carbon dioxide emissions. The palm is coated with black New Foam Technology nitrile, providing excellent dexterity and grip. Features touch screen compatible fingertips and a knit wrist cuff for a secure fit. Anti-static/electrostatic compliant for use in an ESD-protected area.



INDUSTRY

Agriculture	General Maintenance
Assembly	General Purpose
Automotive	Landscaping
Construction	Manufacturing

Features

- 15-gauge rPET/nylon/spandex shell offers bare hand sensitivity
- Nitrile-coated palm with New Foam Technology finish allows hands to breathe while providing great grip in wet, oily, or dry conditions
- Made with rPET (recycled polyester) fiber which utilizes reprocessed PET plastic bottles as an environmentally conscious method to help reduce carbon dioxide emissions. This process helps to reduce 227 grams of carbon dioxide emission, 0.387 kWh of electricity, and over 1 gallon of water per pair

- Touch screen compatible fingertips
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use
- Anti-static/electrostatic compliant
- EN 388:2016 + A1:2018 Levels: 4131A

- EN 407:2020 Levels: X1XXXX
- Cut Level A1

Meets ANSI/ISEA 105-2016 standard

- ASTM F2992-15 Results = 330 grams
- Abrasion Level 3
- Puncture Level 2
- Puncture Results: 42 Newtons

ITEM 600NFT

SIZES 10(XL)-11(2XL)



Specifications

SHELL	SHELL COLOR	GAUGE	COATING	COATING COLOR	COATING TYPE	FINISH	CUFF	TOUCH SCREEN	CUT
rPET/Nylon/Spandex	Gray and Black	15-Gauge	Nitrile	Black	Palm	New Foam Technology	Knit Wrist	Yes	Level A1
ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	ANTI-STATIC/ELECTROSTATIC	EN 388 LEVELS	EN 407 LEVELS			
330 Grams	Level 3	Level 2	42 Newtons	Compliant	4131A	X1XXXX			

Packaging

	QUANTITY	10(XL)	11(2XL)
INNER PACK UPC	12/PACK	810033294815	810033294822
CASE GTIN	6 PK/CASE	10810033294812	10810033294829
CASE WEIGHT (IN POUNDS)		9.9	10.25
OVERCAST COLOR		Black	Light Blue



763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com

13915 Radium St NW
Ramsey, MN 55303