

Samurai Glove® Cut Resistant Low Temperature Gloves

Description

These insulated gloves are constructed with a 10-gauge Tuffalene® UHMWPE shell with a brushed acrylic terry cloth interior for excellent warmth and comfort. The shell is enhanced with a double-dipped palm with three-quarter solid rubber latex and foam rubber latex which provides excellent grip, abrasion resistance, puncture resistance, and water resistance.



INDUSTRY

Automotive	Farming
Carpentry	Landscaping
Cold Storage	Material Handling
Construction	Warehousing

ITEM **CR330INT**

SIZES **8(M)-10(XL)**



Features

- One-piece enhanced Tuffalene® UHMWPE seam-free shell with brushed acrylic terry cloth liner for warmth and comfort
- Double-dipped natural rubber latex palm for high gripping qualities, abrasion resistance, puncture resistance and water resistance
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use
- EN 388:2016 + A1:2018 Levels: 3X42D

Meets ANSI/ISEA 105-2016 standard

- Cut Level A4
- ASTM F2992-15 Results = 1,598 grams
- Abrasion Level 4
- Puncture Level 3
- Puncture Results: 91 Newtons

Specifications

SHELL	SHELL COLOR	GAUGE	LINER	COATING	COATING COLOR	COATING TYPE	CUFF	FINISH	CUT
Tuffalene® UHMWPE	White and Blue	10-Gauge	Brushed Acrylic Terry Cloth	Rubber Latex	Black	Palm over 3/4	Knit Wrist	Foam over Smooth	Level A4
ASTM F2992-15 RESULTS		ABRASION	PUNCTURE	PUNCTURE RESULTS		EN 388 LEVELS			
1,598 Grams		Level 4	Level 3	91 Newtons		3X42D			

Packaging

	QUANTITY	8(M)	9(L)	10(XL)
INNER PACK UPC	12/PACK	0816368029108	816368029115	816368029122
CASE GTIN	6 PK/CASE	10816368029105	10816368029112	10816368029129
CASE WEIGHT (IN POUNDS)		23.5	26.1	30.3
OVERCAST COLOR		Green	Brown	Black



763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com

13915 Radium St NW
Ramsey, MN 55303