

**DOUBLE-PLY MEDIUM WEIGHT CUT RESISTANT SLEEVES**

A range of comfortable cut resistant sleeves containing heat resistant properties.

**FEATURES**

- › Cut resistant: Level C / ANSI A3
- › Thumbhole prevents slipping and wrist exposure
- › Gives increased protection from cuts, slash, tear and punctures
- › Machine knitted double-ply medium weight sleeve
- › Comfortable and protective, the seamless knitted liner avoids skin irritation and is elasticated for extra protection
- › Resistance to contact heat up to 250°C
- › Machine washable
- › Available in two lengths - 14" , 18"
- › Ambidextrous



**SUITABLE FOR**

**Typical Industries**

- Aerospace
- Automotive
- Glass
- Manufacturing
- Paper and Pulp
- Plastics
- Steel

**Suitable Applications**

- Castings
- Handling Large Sheets of Materials with Sharp Edges
- HVAC
- Sheet Metal Handling

**CERTIFICATION**

CAT II



EN 388:2016




2X41C

EN 407:2004



X2XXXX

ANSI/ISEA 105



See overleaf for explanation

### PRODUCTION INFORMATION

MATERIALS	LINER:	Para-aramid
	COATING:	N/A
COLOUR	Yellow	
LENGTH (mm)	14", 18"	
CUFF STYLE	Elasticated	

### ORDERING DETAILS

SIZE	CODE	PACKAGING
14"	SKG00037CZ	96 pieces per case
18"	SKG00038CZ	

### RECOMMENDATIONS FOR USE

- USE: Cut and heat resistant sleeve. Not suitable for high contact heat (beyond 250°C/482°F), electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

### CERTIFICATION LEGENDS

**MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

**CLASSIFICATION FOR CUT RESISTANCE**

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

**HEAT AND FIRE EN 407**

**PERFORMANCE LEVELS**

0-4	0-4	0-4	0-4	0-4	0-4
Contact Heat Resistance	Convective Heat Resistance	Radiant Heat Resistance	Resistance to Small Drops Of Molten Metal	Resistance to Large Splashes of Molten Metal	Burning Behaviour

## GLOBUS

**EUROPE**  
[www.globusgroup.com](http://www.globusgroup.com)  
**E:** sales@globus.co.uk  
**T:** +44 (0)161 877 4747  
**F:** +44 (0)161 877 4746

**MIDDLE EAST & AFRICA**  
[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)  
**E:** gcc@globusgroup.com  
**T:** +971 4 882 9962  
**F:** +971 4 882 9963

**GLOBUS AMERICAS**  
[www.globusgroup.com](http://www.globusgroup.com)  
**E:** americas@globusgroup.com