CUT PROTECTION

Benchmark BMG784



ULTRA LIGHTWEIGHT, EXTREME CUT RESISTANT GLOVES WITH NITRILE FOAM

Using the latest innovation, BMG784 is a very light weight glove (18 gauge) providing outstanding cut protection and high dexterity in the most risky applications. Thin, Breathable and long lasting coating, ideal for all precise applications.

FEATURES

- > Extreme cut resistance: Level F (EN 388:2016)
- 18 gauge seamless liner offers flexibility, comfort and high fingertip sensitivity
- > HPPE on the inside provides comfort and protection
- Specific metal fibre and nylon on the outside, fully encapsulated enable extreme cut protection against burrs and sharp edges
- Nitrile foam coating gives exceptional grip in oily conditions while allowing warm air and moisture from inside to escape, keeping your hands dry and comfortable
- > Reinforced thumb crotch enhances durability
- > Designed for easy movement and continuous wear
- > Breathable back of hand to reduce perspiration
- > Seamless knit prevents irritation
- > Elasticated wrist provides a secure fit









SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Transport

Suitable Applications

- Assembly
- Handling Sharp and Greasy Parts
- Machining
- Bodywork
- Precision Mechanics

CERTIFICATION



See overleaf for explanation



Benchmark BMG784



PRODUCT INFORMATION

MATERIALS	LINER:	18 gauge HPPE, nylon, metal fiber	
	COATING:	Foam nitrile	
COLOUR	Green/Black		
LENGTH (mm)	250 (Size Dependent)		
CUFF STYLE Elasticated knit wrist		knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	BMG00784ED BMG00784EF BMG00784EH BMG00784EJ BMG00784EL	10 pairs per bag 120 pairs per case

CERTIFICATION LEGENDS

규



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE				
Measured breakthrough time	Permeation performance index (grams)			
A1	≥ 200			
A2	≥ 500			
A3	≥ 1000			
A4	≥ 1500			
A5	≥ 2200			
A6	≥ 3000			
A7	≥ 4000			
A8	≥ 5000			
A9	> 6000			

RECOMMENDATIONS FOR USE

machines if there is a risk of entanglement

CLEANING: To clean, wipe with a damp cloth.

away from direct sunlight

damage is present.

 USE: General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving

• STORAGE: Store in dry conditions in the original packaging and

 LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no

GLOBUS

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +97148829962
- F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575) UKCA compliance certificate delivered by the notified body ITS Testing Services UK Ltd, Centre Court, Meridian Business Park, Leicester, LE19 1WD, United Kingdom (Approved Body No. 0362)

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

©2024 Globus (Shetland) Ltd | BMK-DATA-BMG784_0224_1

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.