



Argon Xtra™

INSULATED GLOVE WITH FLEXIBLE PVC SPONGE TOUCH COATING

Lightweight, fleece-lined glove with a flexible PVC sponge touch coating using Hydropellent Technology (HPT). The undulating pattern on the palm enhances grip in oily, wet and dry conditions.

FEATURES

- › Fully dipped
- › Soft fleece lining for comfort in cold conditions
- › Undulating contour grip pattern to the palm
- › Hydropellent Technology repels liquids
- › Good grip in wet and greasy conditions
- › Durable PVC sponge touch finish
- › Sanitised® antimicrobial finish provides extra freshness



SUITABLE FOR

Typical Industries

- Food
- Manufacturing
- Maintenance
- Municipal Services
- Oil and Gas
- Utilities

Suitable Applications

- Cold Storage
- Mechanical Handling in Cold
- Conditions
- Outdoor General Handling
- Packaging
- Warehousing and Distribution

CERTIFICATION



EN 388:2016



3131X

EN511: 2006



120

See overleaf for explanation



Argon Xtra™

PRODUCTION INFORMATION

MATERIALS	LINER:	13 gauge nylon, fleece
	COATING:	PVC HPT
COLOUR	Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SKY911	10 pairs per bag
8/M	SKY912	
9/L	SKY913	
10/XL	SKY914	
11/XXL	SKY915	60 pairs per case

RECOMMENDATIONS FOR USE

- **USE:** Cold resistant glove. Not suitable for thermal (heat), electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



COLD HAZARDS EN 511 PERFORMANCE LEVELS

0-4	0-5	0 or 1
Convective Cold Resistance	Contact Cold Resistance	Water Permeability

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. (Notified Body No. 2777)