ALPHA C SERIES - C-2V

P2 DISPOSABLE RESPIRATOR



The C Series is a lightweight low profile twin fold disposable respirator featuring a unique pleat design that enables the wearer to talk without compromising fit.

KEY FEATURES

- Twin fold design, flexes whilst talking to maintain seal and enables easy storage in a pocket
- Soft lightweight fabric provides comfortable face seal
- Large surface area of filter media lowers breathing resistance
- Low profile exhalation valve to reduce heat and moisture build up
- Colour coded filter media for ease of identification
- Conforms to EN149: 2001 + A1: 2009 FFP2 NR D



TWIN FOLD DESIGN
Ideal for easy storage
in a pocket

LARGE SURFACE AREA Helps lower breathing resistance

LOW PROFILE EXHALATION VALVE Helps to reduce heat and moisture build up







ORDERING INFORMATION

Part Number: C-2V

Packaging: 20 singles per box

12 boxes per case

Certification: EN149: 2001 + A1: 2009

FFP2 NR D

SUITABLE APPLICATIONS

Protects from non-toxic dusts and oil/water based particulates. Some suitable applications include:

- Craft Work
- Iron and Steel Industry
- Mining
- Underground Civil Engineering
- Woodworking
- Welding Work
- Cutting and Casting of Metals
- Hospital
- Laboratory and Disease Control



LPHA C SERIES - C-2V



P2 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

COMPONENT	MATERIAL			
Outer Layer:	Polypropylene Non-Woven			
Central Stiff Layer:	Polyester Fabrics			
Filter Media:	High Filtration Efficiency Melt-Blown (Polypropylene)			
Inner Layer:	Polypropylene Non-Woven			
Nose Piece:	Iron Wire with Polyethylene Plastic Coating			
Nose Pad:	Polyethylene [PE] Foam			
Headband:	Latex-Free Synthetic Rubber			
Headband Staple:	Zinc Metal Wire			
Exhalation Valve: Valve Housing:	Polypropylene			
Valve Membrane	Silicone Rubber			

DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	
Respirator	212	84	128	
Nose Pad	171	20	2	
Nose Piece	90	20	1.2	
Headband	210	4.8	0.4	
Exhalation Valve	41.3	38.2	12.1	

CERTIFICATION

= Recommended = Alternative

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes, MK5 8PP, United Kingdom. [N.B. No.0086].

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

Approval EN 149:2001 + A1:2009	Mesh Colour	Product Codes	APF (Assigned Protection Factor) (x WEL)	Non-Toxic Dusts	VeryFine / Toxic Dusts / Mists / Fumes	Metal Fumes	Oil/Water Based Particulates
FFP1 NR D	White	C-1	4				
FFP2 NR D	Blue	C-2	10	0		0	
FFP2 NR D	Blue	C-2V	10	0		0	
FFP3 NR D	Orange	C-3V	20	0			

www.alphasolway.com T: +44 (0)1461 202452 E: alphasolway.sales@globusgroup.com

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

