



CN741

100% BIODEGREADABLE NITRILE GAUNTLET WITH HIGH GRIP PROPERTIES, LENGTH 38CM, 0.38MM THICK

Offering high resistance to chemicals and excellent grip properties. 100% biodegradable using Eco Best Technology®

FEATURES

- › A fine, supple glove (0.38 mm thick)
- › Nitrile protects the hand from oils, hydrocarbons and grease penetration
- › Wave pattern finish provides a tactile feel, long-lasting grip and control in wet and oily conditions
- › Flock-lined for extra comfort and ease of donning
- › Eco Best Technology® enables the glove to biodegrade once disposed of in landfill
- › Innovative technology on the inside
- › Impermeable for working in damp environments
- › Designed for easy movement and continuous wear
- › Good abrasion resistance
- › Anatomically formed



SUITABLE FOR

Typical Industries

- Agriculture
- Chemical
- Construction
- Fishing/Marine
- Food
- Manufacturing
- Pharmaceutical

Suitable Applications

- Assembly
- Chemical Processing
- Cold (ice) parts handling
- Food Handling
- Handling Wet Objects
- Heavy Duty Handling
- Plant Maintenance

CERTIFICATION

CAT III	EN 388:2016	EN ISO 374-1:2016/Type A	EN ISO 374-5:2016	
UK CA	CE			
2777	4XX1X	AJKLM-NOPT	Virus	

See overleaf for explanation





CN741

PRODUCT INFORMATION

MATERIALS	LINER:	Cotton flock
	COATING:	Nitrile
COLOUR	Navy Blue	
LENGTH (mm)	380 (size dependent)	
CUFF STYLE	Gauntlet	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SHO7411	12 pairs per bag 72 pairs per case
8/M	SHO7412	
9/L	SHO7413	
10/XL	SHO7414	
11/XXL	SHO7415	


RECOMMENDATIONS FOR USE

- **USE:** Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid	C	≥10 min for at least 1 chemical
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofuran	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2023 Globus (Shetland) Ltd | SHO-DATA-CN741-0423_1