



ULTRA LIGHTWEIGHT KNUCKLE COATED GLOVE WITH GREAT OIL GRIP

A very thin, flexible and dexterous knuckle coated glove offering outstanding tactility and grip in wet and oily conditions.

FEATURES

- › Helps to protect the hand from oils, hydrocarbons, grease and abrasion to end of coated area
- › Supple and soft 18 gauge nylon liner provides excellent fingertips sensibility
- › Nitrile sandy finish on palm offering excellent grip properties in wet and oily conditions
- › Designed for easy movement and continuous wear
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure fit



LIGHTWEIGHT
18gg LINER



SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Manufacturing

Suitable Applications

- Handling oily components
- Maintenance
- Wet works
- Assembly

CERTIFICATION




EN 388:2016



4121X

ANSI/ISEA 105



See overleaf for explanation



PRODUCTION INFORMATION

MATERIALS	LINER:	18 gauge nylon
	COATING:	Nitrile sandy finish on smooth nitrile
COLOUR	Blue / black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SKG00002DD	10 pairs per paper wrap
8/M	SKG00002DF	
9/L	SKG00002DH	
10/XL	SKG00002DJ	
11/XXL	SKG00002DL	120 pairs per case

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for cut, thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

ANSI/ISEA 105-2016 ABRASION RATING CHART

Abrasion Level Rating	0	1	2	3	4	5	6
Gram Load	500	500	500	500	1000	1000	1000
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000

CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575)