



Redox

Medium Weight Palm-Coated Nitrile Glove with High Cut Protection

Durable high cut resistance glove with thermal resistance up to 100°C/212°F for short contact. Outstanding grip in dry handling conditions.

Features

- ▲ Medium-weight 10g liner made of para-aramid and steel fibre to protect against high cut risks
- ▲ Nitrile palm coating offers optimum dry grip and protect from oil and water
- ▲ Contact heat protection up to 100°C / 212°F for a short period (15 sec max)
- ▲ Contact heat protection up to 100°C / 212°F for a short period (15 sec max)
- ▲ Seamless knit prevents irritation
- ▲ Elasticated wrist provides a secure fit

Certifications

ANSI/ISEA
105:2016



EN 388:2016
+ A1:2018



4X44F

EN 407:
2020



X1XXXX

EN 388:
2016



3X44F



Suitable industries & applications

Industries

- ▲ Automotive
- ▲ Construction
- ▲ Steel and Metals
- ▲ Utilities
- ▲ Waste and Recycling
- ▲ Highways and Infrastructure
- ▲ Manufacturing
- ▲ Oil and Gas

Applications

- ▲ Vehicle Repairs and Maintenance
- ▲ Civil Engineering
- ▲ Component and Product Assembly
- ▲ Metal Forging and Processing
- ▲ Metal Fabrication Work
- ▲ Public Works

Redox

Medium Weight Palm-Coated Nitrile Glove with High Cut Protection

Product information

Materials	Liner:	10 Gauge Para-Aramid, Steel Fibre, Nylon
	Coating:	Nitrile
Color	Yellow / Black	
Length	4in	
Cuff Style	Elasticated Knit Wrist	

Ordering information

7/S	SKG00106CD-7(S)	Items per Pack 12 x Pairs
8/M	SKG00106CF-8(M)	
9/L	SKG00106CH-9(L)	Items per Case 72 x Pairs
10/XL	SKG00106CJ-10(XL)	
11/2XL	SKG00106CL-11(2XL)	

Additional information

Certification legend




or click [here](#)

Declaration of conformity



or click [here](#)

View product online



or click [here](#)