

SINGLE USE EXAMINATION GLOVE, 100% VINYL, POWDER FREE, 240MM LONG, 0.08MM THICK, CLEAR COLOUR

High performance, powder-free, vinyl single use examination glove. Dual certified (Industrial and Medical) and food safe.

FEATURES

- › The premium quality PVC leads to an excellent tactile sensitivity and a higher tensile strength
- › Palm thickness 0.08mm, weight: 4.5g, size: M
- › Powder-free, latex free, non-sterile, AQL 1.5
- › DOP Or DEHP free to minimise the risks of allergic contact dermatitis
- › Durable beaded cuff design enables the glove to be donned and removed efficiently and securely.
- › Approved for food handling
- › Dual labelling: PPE and medical
- › Medical device compliant (MDD 93/42/EEC), conforms to EN455 (all parts)



MEDICAL DEVICE

SUITABLE FOR





Typical Industries

- Healthcare
- Electronics
- Food
- Pharmaceutical
- Manufacturing

Suitable Applications

- Examination
- Food Handling
- Laboratory Analysis
- Light Assembly

CERTIFICATION

<p>CAT III</p>  <p>2777</p>	<p>EN ISO 374-1:2016/ Type B</p>  <p>KPT</p>	<p>EN ISO 374-5:2016</p>  <p>Virus</p>	<p>EN455</p>  <p>MEDICAL DEVICE</p>
--	--	---	--

See overleaf for explanation



VX450™

PRODUCTION INFORMATION

MATERIALS	LINER:	Vinyl
	COATING:	–
COLOUR	Clear	
LENGTH (mm)	240	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00450AB	100 singles per box
7/S	SKG00450AD	
8/M	SKG00450AF	
9/L	SKG00450AH	
10/XL	SKG00450AJ	
		10 boxes per case

RECOMMENDATIONS FOR USE

- **USE:** Single use glove. Not suitable for mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%		
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid		
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide	B	≥30 min for at least 3 chemicals
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)



FOOD CONTACT DIRECTIVE 2002 / 72 EC

EN455-1:	Freedom from holes
EN455-2:	Physical properties
EN455-3:	Biological evaluation
EN455-4:	Shelf Life

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15N2P, Republic of Ireland. (Notified Body No. 2777)