

▲SKYTEC Xenon Plus[™]

HIGH CHEMICAL AND CUT RESISTANT GAUNTLET WITH EXCELLENT GRIP

Triple dipped nitrile gauntlet over a cut resistant liner with a nitrile sandy finish palm providing excellent grip in wet and oily conditions whilst protecting from chemicals.

FEATURES

- > Cut resistance: Level C
- A soft, lightweight and robust glove offering great dexterity
- > Triple coated nitrile provides a strong chemical resistance
- > Superior grip in wet and oily environments
- > Thin cut resistant liner provides medium cut protection whilst being comfortable.
- > Long cuff to provide forearm protection
- > Designed for easy movement and continuous wear
- > No irritation by seams in contact with the skin



SUITABLE FOR

Typical Industries

- Chemical/ Petrochemical
- Construction
- Manufacturing
- Oil and Gas
- Waste

Suitable Applications

- Canning
- Cementing
- Chemical/Oils Parts
- Handling with Cut RisksOil Submersion

CERTIFICATION




10

€€ 0075

See overleaf for explanation





∧SKYTEC Xenon Plus[™]

PRODUCTION INFORMATION

	MATERIALS	LINER:	18g Cut resistant liner	
		COATING:	Nitrile, sandy finish palm	
	COLOUR	Green		
	LENGTH (mm)	350 (Size Dependent)		
	CUFF STYLE	Gauntlet		

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M 9/L 10/XL 11/XXL	SKG00003EF SKG00003EH SKG00003EJ SKG00003EL	10 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE

- USE: Chemical and cut resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

MICAL hanol	CODE J	CHEMICAL n-Heptane	TYPE OF GLOVES	BREAKTHROUGH TIME
tone tonitrile Iloromethane	K L M	Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid	A	≥30 min for at least 6 chemicals
oon Disulfide ene hylamine	N O P	99% Acetic acid 25% Ammonium hydroxide	В	≥30 min for at least 3 chemicals
nyiamine ahydrofurane 1 acetate	furane S	30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehyde	С	≥10 min for at least 1 chemical

GLOBUS

CODE

B

D

G

н

CHEN Meth

Aceto

Aceto

Dichl Carb

Tolue

Diet

Tetra

Ethyl

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +97148829962
- F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575)

www.globusgroup.com

GLOBUS AMERICAS

PROTECTION AGAINST

MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

B

E: americas@globusgroup.com

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

© 2023 Globus (Shetland) Ltd | SKY-DATA-XENON+-1123_1