

HIGH CUT RESISTANT IMPACT GLOVE WITH THUMB CROTCH REINFORCEMENT

A robust and flexible glove offering high cut and impact protection. Excellent grip in wet and oily conditions.

FEATURES

- › Cut resistant: Level E / ANIS A5
- › 13 gauge HPPE, Steel and nylon liner provides excellent comfort and cut protection
- › Excellent grip with a nitrile foam sandy coating on the palm
- › Double dipped on the palm to limit oil penetration
- › Dense, moulded TPR protection zones on knuckles, fingers, thumb and back of hand
- › TPR zones are sewn to the liner for increased lifespan
- › Stitched reinforced thumb crotch for enhanced durability
- › Breathable back of hand to reduce perspiration
- › Elasticated wrist provides a secure fit



SUITABLE FOR

Typical Industries

- Oil and Gas
- Construction
- Mining
- Transport
- Heavy Engineering
- Offshore
- Ports

Suitable Applications

- Demolition
- Drilling
- Extraction
- Heavy handling
- Cargo handling
- Extraction and refining
- Rigging

CERTIFICATION




EN 388:2016 + A1:2018



4X42EP

ANSI/ISEA 105



ANSI / ISEA 138



See overleaf for explanation

PRODUCTION INFORMATION		
MATERIALS	LINER:	13 gauge HPPE, steel fibre, nylon
	COATING:	Sandy nitrile over smooth nitrile (double dipped)
COLOUR	Grey/Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

- | RECOMMENDATIONS FOR USE |
|--|
| <ul style="list-style-type: none"> USE: General handling glove with cut and impact protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement STORAGE: Store in dry conditions in the original packaging and away from direct sunlight CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use |

ORDERING DETAILS		
SIZE	CODE	PACKAGING
8/M 9/L 10/XL 11/XXL	SKG00007HF SKG00007HH SKG00007HJ SKG00007HL	10 pairs per bag 60 pairs per case

CERTIFICATION LEGENDS																																																																																																		
<div style="display: flex; align-items: flex-start;"> <div> <p>MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">0-4</td> <td style="text-align: center;">0-5</td> <td style="text-align: center;">0-4</td> <td style="text-align: center;">0-4</td> <td style="text-align: center;">A-F</td> <td style="text-align: center;">P</td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> </table> <p style="font-size: small;">*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter</p> </div> </div>	0-4	0-5	0-4	0-4	A-F	P																																																							<table border="1" style="width: 100%; border-collapse: collapse; margin-bottom: 20px;"> <thead> <tr> <th colspan="2" style="background-color: #444; color: white;">CLASSIFICATION FOR CUT RESISTANCE</th> </tr> <tr> <th style="background-color: #444; color: white;">Measured breakthrough time</th> <th style="background-color: #444; color: white;">Permeation performance index (grams)</th> </tr> </thead> <tbody> <tr><td>A1</td><td>≥ 200</td></tr> <tr><td>A2</td><td>≥ 500</td></tr> <tr><td>A3</td><td>≥ 1000</td></tr> <tr><td>A4</td><td>≥ 1500</td></tr> <tr><td>A5</td><td>≥ 2200</td></tr> <tr><td>A6</td><td>≥ 3000</td></tr> <tr><td>A7</td><td>≥ 4000</td></tr> <tr><td>A8</td><td>≥ 5000</td></tr> <tr><td>A9</td><td>> 6000</td></tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3" style="background-color: #444; color: white;">CLASSIFICATION FOR IMPACT RESISTANCE</th> </tr> <tr> <th style="background-color: #444; color: white;">Performance level</th> <th style="background-color: #444; color: white;">Mean (kJ)</th> <th style="background-color: #444; color: white;">All impacts (kJ)</th> </tr> </thead> <tbody> <tr><td>1</td><td>≤ 9</td><td>< 11.3</td></tr> <tr><td>2</td><td>≤ 6.5</td><td>≤ 8.1</td></tr> <tr><td>3</td><td>≤ 4</td><td>≤ 5</td></tr> </tbody> </table>	CLASSIFICATION FOR CUT RESISTANCE		Measured breakthrough time	Permeation performance index (grams)	A1	≥ 200	A2	≥ 500	A3	≥ 1000	A4	≥ 1500	A5	≥ 2200	A6	≥ 3000	A7	≥ 4000	A8	≥ 5000	A9	> 6000	CLASSIFICATION FOR IMPACT RESISTANCE			Performance level	Mean (kJ)	All impacts (kJ)	1	≤ 9	< 11.3	2	≤ 6.5	≤ 8.1	3	≤ 4	≤ 5
0-4	0-5	0-4	0-4	A-F	P																																																																																													
CLASSIFICATION FOR CUT RESISTANCE																																																																																																		
Measured breakthrough time	Permeation performance index (grams)																																																																																																	
A1	≥ 200																																																																																																	
A2	≥ 500																																																																																																	
A3	≥ 1000																																																																																																	
A4	≥ 1500																																																																																																	
A5	≥ 2200																																																																																																	
A6	≥ 3000																																																																																																	
A7	≥ 4000																																																																																																	
A8	≥ 5000																																																																																																	
A9	> 6000																																																																																																	
CLASSIFICATION FOR IMPACT RESISTANCE																																																																																																		
Performance level	Mean (kJ)	All impacts (kJ)																																																																																																
1	≤ 9	< 11.3																																																																																																
2	≤ 6.5	≤ 8.1																																																																																																
3	≤ 4	≤ 5																																																																																																

GLOBUS

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.