

HIGH CUT RESISTANT IMPACT GLOVE WITH EXTENDED THUMB SHIELD

A flexible seamless cut resistant level E glove with foam nitrile on the palm to maximize grip. Ergonomic TPR design allows outstanding flexibility

FEATURES

- › Cut resistance: level E / ANSI A5
- › 13 gauge (HPPE, steel) liner offers great dexterity for fine handling
- › Excellent grip with a nitrile foam sandy coating on the palm
- › Dense, moulded TPR protection zones on knuckles, fingers, thumb and back of hand
- › Ergonomically designed TPR follow the hand movement reducing hand fatigue
- › TPR zones are sewn to the liner for increased resistance
- › Elasticated wrist provides a secure fit



SUITABLE FOR

Typical Industries

- Oil and Gas
- Construction
- Mining
- Transport
- Heavy Engineering
- Offshore
- Ports

Suitable Applications

- Demolition
- Drilling
- Extraction
- Heavy handling
- Cargo handling
- Extraction and refining
- Rigging

CERTIFICATION




EN 388:2016
+A1:2018



4X42EP

ANSI/ISEA 105



ANSI / ISEA 138



See overleaf for explanation

PRODUCTION INFORMATION		
MATERIALS	LINER:	13 gauge HPPE, steel fibre, nylon
	COATING:	Sandy nitrile
COLOUR	Grey/Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS		
SIZE	CODE	PACKAGING
8/M	SKG00010HF	10 pairs per bag
9/L	SKG00010HH	
10/XL	SKG00010HJ	60 pairs per case
11/XXL	SKG00010HL	
12/XXXL	SKG00010HN	

- ### RECOMMENDATIONS FOR USE
- USE: General handling glove with cut and impact protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
 - STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
 - CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
 - LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

Abrasion Resistance Circular Blade Cut Resistance Tear Resistance Puncture Resistance Straight Blade Cut Resistance (EN ISO: 13997) Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE	
Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

CLASSIFICATION FOR IMPACT RESISTANCE		
Performance level	Mean (kJ)	All impacts (kJ)
1	≤ 9	< 11.3
2	≤ 6.5	≤ 8.1
3	≤ 4	≤ 5

ANSI/ISEA PUNCTURE RESISTANCE	
ANSI Puncture Level	Puncture Resistance (newtons)
1	10-19
2	20-59
3	60-99
4	100-149
5	150+

Puncture Resistance (ANSI/ISEA 105): Puncture resistance is determined by the max force that it takes, exerted from a probe, to puncture the fabric.

GLOBUS

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA