Benchmark

BM18



Wrap-Around Style Safety Spectacle

FEATURES

- Close-fitting protection
- > Universal nose bridge
- > Slim temple tips
- > Anti-scratch lens
- > Lightweight: only 23g
- > Optical class 1 Polycarbonate lens





CERTIFICATION

ITEM NO.	VERSIONS		LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
BME00018KZ	CLEAR	\circ	2C-1.2 ▶ 1FT (€ Z87+ U6	▶ EN 166 FT C € CA Z87+ BM18	Impacts, UV radiations	Anti-scratch
BME00018TZ	DARK GREY		5-3.1 ▶ 1FT (€ Z87+ U6 L3	▶ EN 166 FT C € CA Z87+ BM18	Impacts, UV and Sun glare	Anti-scratch



Benchmark

BM18



GENERAL SPECIFICATIONS

LENS BASE	10mm
WEIGHT	23g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSEBRIDGE	Polycarbonate	Single piece, moulded with side protection
TEMPLE	Polycarbonate	Robust and durable
HINGE	Stainless steel	Hard wearing

LENS MARKINGS

LENS FILTER TYPE:

2C UV

5 Solar

SCALE NUMBER (SHADE):

1.2 Clear

3.1 Dark Grey

▶ Identity of the manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures
- C€ Certification mark

FRAME MARKINGS

Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures
- C€ Certification mark
- Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged

also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a

microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

EUROPE

www.globus.co.uk

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com **T:** +971 4 882 9962

F: +971 4 882 9963

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



© 2019 Globus (Shetland) Ltd | BMK-DATA-BM18-0523_1

EC-Type certification issued by

DGS0: CERTOTICA SCARL, Zona Industriale Villanova, 32013 - Longarone (BL), Italy. 0194: INSPEC, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, UK. 0321: SATRA, Windham Way, Telford Way, Kettering, NN16 8SD, UK. 1105: CCQS UK Ltd, 5 Harbour Exchange Square, London, E14 9GE, UK. 0196: DIN CERTCO, Gesellschaft für Konformitätsbewertung mbH, Alboinstr. 56, D-12103, Berlin. 0403: FIOH, P.O. Box 40, FI-00032.