

SKYTEC™ TRC702

A LIGHTWEIGHT AND DURABLE PU COATED GLOVE WITH MEDIUM CUT PROTECTION. MADE WITH RECYCLED POLYESTER

TRC702 is a supple and lightweight glove offering a good cut resistant barrier whilst maintaining dexterity and comfort. The flexible PU coating enables a secure grip in greasy and dry conditions. Ideal for handling small components with sharp edges.

FEATURES

- › Cut resistant: Level C / ANSI A3
- › A flexible and comfortable glove offering great dexterity
- › HPPE on the inside provides comfort and protection
- › PU coating gives exceptional abrasion resistance and sensitivity allowing workers to handle small pieces
- › Designed for easy movement and continuous wear
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › RCS (Recycled Claim Standard) certified
- › 1 pair = 1PET bottle of 500ml recycled
- › 26g of CO₂ reduced vs virgin polyester alternative







CUT LEVEL
C



RECYCLED 100
claim standard



Part of the
Tricolore Range™






ECO

SUITABLE FOR

- | | |
|--|--|
| <p>Typical Industries</p> <ul style="list-style-type: none"> ▪ Automotive ▪ Construction ▪ Logistics ▪ Manufacturing ▪ Utilities | <p>Suitable Applications</p> <ul style="list-style-type: none"> ▪ Assembly ▪ Handling sharp and greasy Parts ▪ Maintenance ▪ Light fabrication ▪ Precision Mechanics |
|--|--|

CERTIFICATION

<p>CAT II</p> 	<p>EN 388:2016</p>  <p>4X43C</p>	<p>ANSI/ISEA 105</p> 
<p><i>See overleaf for explanation</i></p>		

**PRODUCTION INFORMATION**

MATERIALS	LINER:	13 gauge HPPE, glass fibre, recycled polyester
	COATING:	Polyurethane (PU)
COLOUR	Orange/Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00013GB	10 pairs per paper wrap
7/S	SKG00013GD	
8/M	SKG00013GF	
9/L	SKG00013GH	
10/XL	SKG00013GJ	120 pairs per case
11/XXL	SKG00013GL	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS**MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

GLOBUS**EUROPE**

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575)