Vise Gripster® Mechanics Style Rubber Coated Gloves with Cut, Abrasion, and Puncture Resistance

Description

These general-purpose gloves are palm-dipped with black etched rubber on a seamless 10-gauge red polyester/cotton shell. They have a hook-and-loop closure on a knit wrist to provide an excellent fit. These gloves offer outstanding gripping power and better wear than mechanic-type gloves for a fraction of the cost.

Each pair is individually hang-tagged for retail sale.

INDUSTRY	
Industrial	Construction
Mechanical	Warehousing
Tool Handling	Building
Parts Handling	Manufacturing

ITEM 300RV **SIZES** 8(M)-9(L)

CUT LEVEL A2 | ABRASION LEVEL 3 | PUNCTURE LEVEL 4 | EN 388 2143X | RETAIL READY

Features

- Puncture-resistant, etched-rubber palm retains flexibility
- and grip in low temperatures
- Polyester/cotton 10-gauge shell for comfort
- Hook-and-loop closure secures gloves to wrist to prevent loss or slipping
- EN 388 Levels: 2143X

Meets ANSI/ISEA 105-2016 standard

- Cut Level A2 (palm), Level A1 (back of hand)
- ASTM F2992-15 Results = Palm: 677 grams, Back of Hand: 416 grams
- Abrasion Level 3
- Puncture Level 4
- Puncture Results: 111 Newtons

Specifications

SHELL	SHELL COLOR	COATING	COATING TYPE	COATING COLOR	GAUGE	FINISH	CUFF
Polyester/Cotton	Red	Rubber Latex	Palm	Black	10-Gauge	Etched	Hook-and-Loop

RETAIL READY	CUT	ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS
Yes	Palm = Level A2, Back of Hand = Level A1	Palm = 677 Grams, Back of Hand = 416 Grams	Level 3	Level 4	111 Newtons	2143X

Packaging

	QUANTITY	8(M)	9(L)
PAIR UPC	1	856187001138	856187001114
INNER PACK UPC	12/PACK	810292028008	810292028015
CASE GTIN	6 PK/CASE	10810292028005	10810292028012
CASE WEIGHT (IN POUNDS)		19	20

GGS™

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com

13915 Radium St NW
Ramsey, MN 55303