SPEARFISH® READERS

PFT

BULLHEAD SAFETY® EYE PROTECTION

BH225320PFT

Retainer cord included with each pair of Spearfish® glasses.

LENS Smoke Performance Fog Technology 2.0 Diopter Bifocal Reader Style

FRAME Shiny Black

DESCRIPTION

The Spearfish® has a flexible frame with vented temples, a TPR nose piece, and TPR temple ends. Designed to contour with the natural curvature of the head, the Spearfish® maximizes all-day wearability and comfort. Bifocal reader style lenses feature a magnification diopter positioned at the bottom inside of the lens. This improves workplace safety by eliminating the need to switch between safety and reading glasses. The BH225320PFT also features a PFT lens. Thanks to its chemical and physical properties, Performance Fog Technology is a permanent coating that prevents the formation of condensation on the lenses by absorbing the humidity drops.

Each dozen is packaged in a retail-ready box.

TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses constructed with the highest quality polycarbonate and frames made with nylon.

- Z87+ — MEETS ANSI/ISEA Z87.1-2020 STANDARDS
- ANSI/ISEA Z87.1-2020 ANTI-FOG — MEETS ANTI-FOG STANDARD
- ARC FLASH TESTED — ARC FLASH TESTED TO 35 CAL/CM²
- ERGONOMIC FIT — ERGONOMIC FIT RELIEVES PRESSURE
- HARD COAT — ANTI-SCRATCH HARD COAT TREATED LENS
- PERFORMANCE FOG TECHNOLOGY — PERMANENT HYDROPHILIC COATING
- READER STYLE — INCLUDES MAGNIFICATION DIOPTER
- TAPERED LENS — TAPERED LENS ELIMINATES DISTORTION
- UV PROTECTION — FILTERS 99.9% UVA/UVB/UVC LIGHT RAYS

FEATURES

- PFT - Performance Fog Technology lens: Better than traditional anti-fog! This water-washable, hydrophilic anti-fog lens coating is permanently bonded to the lens to absorb moisture and evenly disperse it, providing clear, fog-free vision
- Each pair includes a retainer cord
- Flexible and lightweight half-frame design
- Dual 8 base curve lenses for full protection and visual correctness
- TPR nose piece and temple ends
- Vented temples increase airflow
- Meets ANSI/ISEA Z87.1-2020 standards
- Meets ANSI/ISEA Z87.1-2020 anti-fog properties standard

SPECIFICATIONS

LENS	LIGHT TRANSMITTANCE	FRAME TYPE	FRAME COLOR	WEIGHT	BASE CURVE	FRAME WIDTH	END OF TIPS WIDTH	TEMPLE LENGTH
Smoke PFT	12%	Vented Half Frame	Shiny Black	24 Grams	8	143 mm	78 mm	102 mm

PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	810033293108	10810033293105	20810033293102

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@BullheadSafety.com

BullheadSafety.com

Bullhead Safety®