

FrogWear® Shoulder Length Triple-Coated PVC Abrasion Resistant Chemical Handling Gloves

Description

These supported chemical handling gloves are shoulder-length, seamless, and specially formulated for handling chemical residues, oils, or greasy materials. The triple-dipped blue PVC stays flexible in temperatures down to -5°F and the sandpaper grip enhances the handling of slippery objects. Includes an antimicrobial-treated 13-gauge cotton liner which helps absorb perspiration from the hand. The sleeve portion is unlined and ends with an elastic cuff for a secure fit.



INDUSTRY

Chemical Handling	Petrochemical
General Cleaning	Maintenance

Features

- Seamless 13-gauge cotton liner helps absorb perspiration
- Antimicrobial treated liner reduces bacteria that cause odors and can lead to dermatitis
- Triple-dipped blue PVC gives protection against water and chemicals
- Rough, sandpaper-finish palm is excellent for wet or dry grip
- Flexible
- Chemical resistant
- Includes sizing options not common in most chemical gloves
- Shoulder length to protect from spills and splashes
- Anti-static/electrostatic compliant
- EN 388 Levels: 4121X
- EN ISO 374-1:2016/Type B: JKL

ITEM **8690**

SIZES **9(L)-10(XL)**



Meets ANSI/ISEA 105-2016 standard

- Cut Level A1
- ASTM F2992-15 Results = 402 grams
- Abrasion Level 5
- Puncture Level 2
- Puncture Results: 28 Newtons

Specifications

LINER	GAUGE	COATING	COATING TYPE	COATING COLOR	FINISH	LENGTH	CUFF	CUFF LENGTH	ANTIMICROBIAL PROTECTION
Cotton	13-Gauge	Triple PVC	Full	Blue	Sandpaper	24 in.	Elastic End	Shoulder	Yes
ANTI-STATIC/ELECTROSTATIC	CUT	ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS	EN ISO 374-1:2016/TYPE B		
Compliant	Level A1	402 Grams	Level 5	Level 2	28 Newtons	4121X	JKL		

Packaging

	QUANTITY	9(L)	10(XL)
PAIR UPC	1	NA	NA
INNER PACK UPC	12/PACK	816679017221	816679017238
CASE GTIN	1 PK/CASE	10816679017228	10816679017235
CASE WEIGHT (IN POUNDS)		8.29	8.8



763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com

13915 Radium St NW
Ramsey, MN 55303