FrogWear® Premium Neoprene Rough Etched Finish 18-Inch Chemical Handling Gloves

Description

These heavy-wall supported chemical handling gloves are multi-dipped in premium-grade heavy black neoprene for superior quality and durability. They grant protection against chemicals, acids, and solvents. They also offer excellent all-around protection against abrasion hazards. The rough etched finish is excellent for applications where a wet grip is required. Features an antimicrobial-treated cotton interlock liner that reduces bacteria. The gloves are 18 inches long with a gauntlet cuff for extended arm protection.

INDUSTRY	
Material Handling	Petrochemical
Cleaning	Kitchen Cleaning
Chemical Processing	Degreasing
Mining	Oil and Gas Refining

Features

- Component materials comply with FDA regulations for food contact
- Multi-dipped in premium-grade black neoprene
- Soft cotton interlock liner is permanently adhered to the shell and adds extra comfort plus durability
- Rough-etched finish enhances grip in wet or greasy situations and provides extended wear
- Antimicrobial treated liner reduces bacteria that cause odors and can lead to dermatitis
- 18-inch length extends protection up the arm
- Excellent wet grip
- Protection against alkaline and acids

ITEM 9918R **SIZES** ONE SIZE

CUT LEVEL A2 | ABRASION LEVEL 4 | PUNCTURE LEVEL 2 | HEAT LEVEL 3 | FDA COMPLIANT | EN 388 3121X

Meets ANSI/ISEA 105-2016 standard

- Cut Level A2
- ASTM F2992-15 Results = 752 grams
- Abrasion Level 4
- Puncture Level 2
- Puncture Results: 50 Newtons
- Conductive Heat Level 3
- Resistant to solvents, greases, and oils
- Gauntlet cuff allows for easy donning and removal plus extra forearm protection
- EN 388 Levels: 3121X
- EN ISO 374-1:2016/Type B: AKLPT
- EN 407 Levels: X3XXXX

Specifications

LINER	COLOR	COATING	FINISH	LENGTH	CUFF	ANTIMICROBIAL PROTECTION	FDA FOOD CONTACT	CUT	ASTM F2992-15 RESULTS
Cotton Interlock	Black	Triple Neoprene	Rough Etched	18 in.	Gauntlet	Yes	Compliant	Level A2	752 Grams

ABRASION	PUNCTURE	PUNCTURE RESULTS	CONDUCTIVE HEAT	EN 388 LEVELS	EN ISO 374-1:2016/TYPE B	EN 407 LEVELS
Level 4	Level 2	50 Newtons	Level 3	3121X	AKLPT	X3XXXX

Packaging

	QUANTITY	ONE SIZE
PAIR UPC	1	N/A
INNER PACK UPC	12/PACK	816679017429
CASE GTIN	3 PK/CASE	10816679017426
CASE WEIGHT (IN POUNDS)		30.1

Permeation Data

EN ISO 374-01: 2016	Chemical	PL
A	Methanol	3
K	Sodium Hydroxide 40%	6
L	Sulfuric Acid 96%	2
P	Hydrogen Peroxide 30%	6
T	Formaldehyde 37%	6

Permeation data was measured in two ways:

1. For solvents – Gas Chromatography
2. For acid and bases – By conductivity measurements

* PL = Perfomance level

GGS™

763-450-0110
Sales@GlobalGlove.com
GlobalGlove.com
13915 Radium St NW
Ramsey, MN 55303