Vise Gripster® C.I.A. Cut, Impact, Abrasion, and Puncture Resistant Nitrile Coated Gloves with Hook-and-Loop Knit Wrist - LIMITED STOCK

Description

These cut and impact-resistant gloves feature a 13-gauge yellow-and-black seamless Aralene® (enhanced aramid fiber) shell. Double-dipped with a smooth nitrile base dip underneath a black Mach Finish nitrile palm coating. The gloves are enhanced with a reinforced thumb crotch and padding sewn inside the palm for added durability. TPU impact protection shields the fingers and metacarpal bones. Sewn with aramid fiber for added cut and heat resistance. The hook-and-loop closure provides a secure fit.

INDUSTRY	
Glass Handling	Construction
Bottle Handling	Metal Fabrication
Automotive	Metal Stamping
Aerospace	Oil and Gas

Features

- 13-gauge Aralene® (enhanced aramid fiber) shell offers cut and heat resistance
- Abrasion-resistant Mach Finish nitrile offers excellent grip in wet and oily conditions
- Double coating provides superior grip, abrasion resistance, and protection from liquid saturation
- Soft, flexible, TPU impact protection over the fingers and metacarpal bones provides tough protection
- Padded palm increases comfort and dampens vibration
- Reinforced thumb crotch increases abrasion resistance in vulnerable area

ITEM CIA609MFV **SIZES** 8(M)-11(2XL)

CUT LEVEL A5 | ABRASION LEVEL 6 | PUNCTURE LEVEL 3 | ANSI / ISEA 138 1 | EN 388 4X31E | EN 407 X2XXXX

- Knit wrist with hook-and-loop closure allows users a secure and comfortable fit
- EN 388 Levels: 4X31E
- EN 407:2020: X2XXXX

Meets ANSI/ISEA 138-2019 standard

- Impact Level (Overall): 1
- Impact Level (Fingers/Thumb): 2
- Impact Level (Knuckles): 1

Meets ANSI/ISEA 105-2016 standard

- Cut Level A5
- ASTM F2992-15 Results = 2,346 grams
- Abrasion Level 6
- Puncture Level 3
- Puncture Results: 70 Newtons

Specifications

SHELL	GAUGE	SHELL COLOR	COATING	COATING TYPE	COATING COLOR	FINISH	PADDED PALM	REINFORCED AREA	CUFF
Aralene®	13-Gauge	Yellow/Black	Nitrile	Palm	Black	Mach Finish	Yes	Thumb Crotch	Knit Wrist with Hook-and-Loop

IMPACT PROTECTION	CUT	ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	IMPACT	EN 388 LEVELS
TPU	Level A5	2,346 Grams	Level 6	Level 3	70 Newtons	Level 1	4X31E

Packaging

	QUANTITY	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	N/A	N/A	N/A	N/A
INNER PACK UPC	12/PACK	816368025964	816368025971	816368025988	816368025995
CASE GTIN	6 PK/CASE	10816368025961	10816368025978	10816368025985	10816368025992
CASE WEIGHT (IN POUNDS)		30.4	32	33	34
OVERCAST COLOR		Green	Brown	Black	Light Blue

GGS™

763-450-0110
Sales@GlobalGlove.com
GlobalGlove.com
13915 Radium St NW
Ramsey, MN 55303