FrogWear® Supported Cotton-Lined Blue Flexible Natural Rubber Latex Gloves

Description

These supported chemical handling gloves are a flexible blue natural rubber latex over a cotton interlock liner which absorbs perspiration. They are 12 inches long with a suede finish for enhanced grip. The liner is treated with Sanitized® antimicrobial protection to prevent and reduce bacterial growth. These gloves have a contoured palm for an excellent fit and have a gauntlet cuff for extended protection up the arm.

INDUSTRY	
Construction	Painting
Fishing	Sheet Metal Work
Glass Handling	Food Processing
Masonry	Agricultural Chemicals

ITEM 212 **SIZES** 7(S)-10(XL)

Features

- Natural rubber latex gloves are resistant to a variety of chemicals
- Sanitized® antimicrobial treated liner reduces bacteria that cause odors and can lead to dermatitis
- Interlock knit cotton liner helps absorb perspiration
- Suede finish enhances grip
- Curved-finger, contoured, blue palm, excellent fit
- Launderable
- Gauntlet cuff allows for easy donning and removal plus extra forearm protection
- EN 388 Levels: 4131X
- EN 407:2020: X2XXXX
- EN ISO 374-1:2016/Type A: AKLMNPST

Specifications

COATING	COATING COLOR	COATING TYPE	LINER	FINISH	LENGTH
Double Rubber Latex	Blue	Full	Knit Cotton Interlock	Suede	12 in.

CUFF	ANTIMICROBIAL PROTECTION	EN 388 LEVELS	EN 407 LEVELS	EN ISO 374-1:2016/TYPE A
Gauntlet	Yes	4131X	X2XXXX	AKLMNPST

Packaging

	QUANTITY	7(S)	8(M)	9(L)	10(XL)
PAIR UPC	1	N/A	N/A	N/A	N/A
INNER PACK UPC	12/PACK	810033291968	816679014183	816679014190	816679014206
CASE GTIN	6 PK/CASE	10810033291965	10816679014180	10816679014197	10816679014203
CASE WEIGHT (IN POUNDS)		24.5	26.4	29.4	30.6

Permeation Data

EN ISO 374-01: 2016	Chemical	PL
A	Methanol	6
K	Sodium Hydroxide 40%	6
L	Sulfuric Acid 96%	4
M	Nitric Acid 65%	6
N	Acetic Acid 99%	3
P	Hydrogen Peroxide 30%	6
S	Hydrofluoric Acid 40%	5
T	Formaldehyde 37%	6
T	Formaldehyde 37%	6

Permeation data was measured in two ways:

1. For solvents – Gas Chromatography
2. For acid and bases – By conductivity measurements

* PL = Perfomance level

GGS™

763-450-0110
Sales@GlobalGlove.com
GlobalGlove.com
13915 Radium St NW
Ramsey, MN 55303