Cut and Impact Resistant Goatskin Leather Insulated Drivers Gloves with Heat Resistant Aralene® Liner

CIA7000INT

7(S)-11(2XL)

Description

These cut and impact-resistant low-temperature gloves have standard-grade white grain goatskin leather. The thin woven yellow Aralene® (enhanced aramid fiber) inner liner provides cut and heat resistance. Features 100 grams of 3M™ Thinsulate™ insulation. The blue, gray, and white flexible TPR impact protection protects the fingers and metacarpal bones on the back of the hand. These gloves include a keystone thumb, gunn cut pattern, and an open cuff for easy donning and doffing.

Each pair is individually packaged in a polybag.

Features and Benefits

- Standard-grade grain goatskin offers ultimate dexterity
- Thin Aralene® (enhanced aramid fiber) liner is sewn into the glove and offers great dexterity, cut resistance, and heat resistance
- 100 grams of 3M™ Thinsulate™ insulation
- Flexible TPR impact protection over the fingers and metacarpal bones provides tough protection
- Gunn cut pattern
- Ergonomic keystone thumb improves durability, comfort, and dexterity while reducing hand fatigue
- Open cuff allows for easy donning and removal
- EN 388:2016+A1:2018 Levels: 3X33EP
- EN 407:2020: X2XXXX

Meets ANSI/ISEA 105-2016 standard

- Cut Level A6
- ASTM F2992-15 Results = 3,116 grams
- Abrasion Level 5
- Puncture Level 4
- Puncture Results: 118 Newtons
- Conductive Heat Level 3

Meets ANSI/ISEA 138-2019 standard

- Impact Level (Fingers/Thumb): 2
- Impact Level (Knuckles): 2
- Impact Level (Overall): 2

ANSI/ISEA 105 A6 5 4 | CUT LEVEL A6 | ABRASION LEVEL 5 | PUNCTURE LEVEL 4 | HEAT LEVEL 3 | ANSI / ISEA 138 2

763-450-0110
Sales@GlobalGlove.com
GlobalGlove.com
13915 Radium St NW
Ramsey, MN 55303

Cut and Impact Resistant Goatskin Leather Insulated Drivers Gloves with Heat Resistant Aralene® Liner

CIA7000INT

7(S)-11(2XL)

Industries

- Agriculture
- Construction
- Demolition
- Maintenance
- Energy
- Manufacturing
- Mining
- Oil and Gas

Applications

- Utilities
- Cold Storage
- Fabrication
- Fracking
- Recycling
- Transportation

Specifications

SHELL	SHELL COLOR	LINER	LINER COLOR	INSULATION	INSULATION AMOUNT	CUFF	IMPACT PROTECTION
Grain Goatskin	White	Aralene®	Yellow	3M™ Thinsulate™	100 Grams	Open	TPR

CUT	ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	CONDUCTIVE HEAT	IMPACT	EN 388 LEVELS	EN 407 LEVELS
Level A6	3,116 Grams	Level 5	Level 4	118 Newtons	Level 3	Level 2	3X33EP	X2XXXX

Packaging

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
INNER PACK UPC	12/PACK	810033299957	810033299964	810033299971	810033299988	810033299995
CASE GTIN	3 PK/CASE	10810033299954	10810033299961	10810033299978	10810033299985	10810033299992
CASE WEIGHT (IN POUNDS)		18.5	23.3	24.4	25.3	26.5
OVERCAST COLOR		White	Green	Brown	Yellow	Gray

763-450-0110
Sales@GlobalGlove.com
GlobalGlove.com
13915 Radium St NW
Ramsey, MN 55303