

Big Ole® Cut, Abrasion, and Puncture Resistant Premium Leather Palm Gloves with Aralene® Liner

Description

These premium-grade split cowhide leather palm gloves have a 9 oz. canvas back and a cut-resistant Aralene® (enhanced aramid fiber) inner liner that also provides heat resistance. The gloves feature a washable double-layer duck safety cuff and are sewn with aramid fiber for added durability. Gunn cut pattern and a wing thumb to reduce hand fatigue.



INDUSTRY

| | |
|-----------------|----------------|
| Construction | Maintenance |
| Lumber Industry | Automotive |
| Forestry | Steel Handling |

Features

- Leather palm wraps around the index finger and thumb for extra protection
- Sewn with aramid fiber for added durability and cut and heat resistance
- Leather knuckle strap
- Overcast color on hem for easy size identification
- Washable double-layer duck safety cuff enhances reusability and allows for fast removal
- EN 407:2020: X2XXXX

Specifications

| SHELL | SHELL COLOR | WEIGHT | PALM | PALM COLOR | GRADE | LINER | LINER COLOR | STITCHING | THUMB |
|-----------------------------------|-------------|----------|-----------------------|------------|----------|------------------|-----------------|-----------|-------|
| 9 oz Canvas | Natural | 9 oz | Split Cowhide | Gray | Premium | Aralene® | Yellow and Gray | Aramid | Wing |
| CUFF | | CUT | ASTM F2992-15 RESULTS | ABRASION | PUNCTURE | PUNCTURE RESULTS | EN 407 LEVELS | | |
| Washable Double Layer Duck Safety | | Level A4 | 1,524 Grams | Level 5 | Level 5 | 152 Newtons | X2XXXX | | |

Packaging

| | QUANTITY | 8(M) | 9(L) | 10(XL) |
|-------------------------|----------|----------------|----------------|----------------|
| PAIR UPC | 1 | N/A | N/A | N/A |
| INNER PACK UPC | 12/PACK | 810292024833 | 810292024840 | 810292024857 |
| CASE GTIN | 3PK/CASE | 20810292024837 | 20810292024844 | 20810292024851 |
| CASE WEIGHT (IN POUNDS) | | 28.5 | 28.6 | 28.7 |
| OVERCAST COLOR | | Green | Brown | Blue |

ITEM **CR2100**

SIZES **8(M)-10(XL)**



Meets ANSI/ISEA 105-2016 standard

- Cut Level A4
- ASTM F2992-15 Results = 1,524 grams
- Abrasion Level 5
- Puncture Level 5
- Puncture Results: 152 Newtons