PUP™ Performance Polyurethane Coated Nylon/Spandex Gloves with Cut, Abrasion, and Puncture Resistance

Description

These lightweight, 15-gauge seamless nylon/spandex gloves are a general-purpose option. The palm has a black polyurethane performance coating with a smooth finish. The knit wrist cuff provides a secure fit for the user.

INDUSTRY	
General Assembly	Painting
Small Parts Handling	Automotive
	General Purpose

ITEM PUP-27 **SIZES** 7(S)-10(XL)

CUT LEVEL A1 | ABRASION LEVEL 3 | PUNCTURE LEVEL 2 | EN 388 4121X

Features

- Polyurethane performance palm is excellent for wet or dry grip and breathability
- 15-gauge nylon/spandex shell offers bare hand sensitivity
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use
- EN 388 Levels: 4121X

Meets ANSI/ISEA 105-2016 standard

- Cut Level A1
- ASTM F2992-15 Results = 208 grams
- Abrasion Level 3
- Puncture Level 2
- Puncture Results: 22 Newtons

Specifications

SHELL	SHELL COLOR	GAUGE	COATING	COATING TYPE	FINISH	CUFF	CUT	ASTM F2992-15 RESULTS	ABRASION
Nylon/Spandex	Black	15-Gauge	PU/Nitrile	Palm	Smooth	Knit Wrist	Level A1	208 Grams	Level 3

PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS
Level 2	22 Newtons	4121X

Packaging

	QUANTITY	7(S)	8(M)	9(L)	10(XL)
PAIR UPC	1	N/A	N/A	N/A	N/A
INNER PACK UPC	12/PACK	816368024516	816368024523	816368024530	816368024547
CASE GTIN	6 PK/CASE	10816368024513	10816368024520	10816368024537	10816368024544
CASE WEIGHT (IN POUNDS)		6.5	7.1	7.9	8.5
OVERCAST COLOR		Red	Green	Brown	Black

GGS™

763-450-0110
Sales@GlobalGlove.com
GlobalGlove.com
13915 Radium St NW
Ramsey, MN 55303