

## Gripster® Cut, Abrasion, Puncture, and Hypodermic Needle Resistant Gloves Made with Alycore® and a High-Visibility Orange Palm

### Description

Featuring a 10-gauge Aralene® (enhanced aramid fiber) shell that provides both cut and heat resistance, these gloves provide extreme cut resistance and hypodermic needle protection with Alycore® inside. The shell is enhanced by a high-visibility orange etched natural rubber latex coated palm. See diagram for a detailed explanation of Alycore® areas. Each pair is individually hang-tagged for retail sale.



INDUSTRY	
Recycling	Forestry
Cable	Lumber Industry
Construction	Rebar Handling
Demolition	Barbed Wire

ITEM **AC600KV** SIZES **8(M)-10(XL)**



### Features

- Alycore® delivers unparalleled results with ultimate technology in the world of cut, puncture, and needle resistance while still remaining lightweight, flexible, breathable, and washable
- Aralene® is an aramid fiber that provides cut and heat resistance
- Puncture-resistant, etched-rubber palm retains flexibility and grip in low temperatures
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use
- Sold by the pair
- EN 388 Levels: 4544F

### Meets ANSI/ISEA 105-2016 standard

- Cut Level A9 palm, bottom of fingers, and thumb
- ASTM F2992-15 Palm Results = >8000 grams
- Non-Alycore® reinforced areas achieve cut level A6
- Hypodermic needle puncture resistance levels: Level 5 (palm), Level 3 (bottom of fingers and thumb)
- Abrasion Level 4
- Puncture Level 5
- Puncture Results: 222 Newtons

### Specifications

SHELL	GAUGE	COLOR	PALM	COATING	COATING TYPE	COATING COLOR	FINISH	
Aralene®	10-Gauge	Yellow	Reinforced Alycore®	Rubber Latex	Palm	High-Visibility Orange	Etched	
CUFF	RETAIL READY	CUT	ASTM F2992-15 RESULTS	NEEDLE	ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS
Knit Wrist	Yes	Level A9/A6	>8000	Level 5/3	Level 4	Level 5	222 Newtons	4544F

### Packaging

	QUANTITY	8(M)	9(L)	10(XL)
PAIR UPC	1	816368026886	816368026893	816368026909
INNER PACK GTIN	12/PACK	10816368026883	10816368026890	10816368026906
CASE GTIN	6 PK/CASE	20816368026880	20816368026897	20816368026903
CASE WEIGHT (IN POUNDS)		32.2	33.7	35.8
OVERCAST COLOR		Green	Brown	Black

Needle resistance level based off third-party independent lab test results using the ASTM F2878-10 standard with 25-gauge needles.



763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

13915 Radium St NW  
Ramsey, MN 55303