DORADO® PFT

PERFORMANCE FOG TECHNOLOGY

BULLHEAD SAFETY® EYE PROTECTION

BH966PFT

BH9G

Optional removable flame-resistant foam gasket is available for all Dorado® safety glasses.

*Optional see below

LENS Indoor/Outdoor Performance Fog Technology

FRAME Matte Black

DESCRIPTION

The lightweight, contemporary full frame of the Dorado® features dual lenses for improved protection and 100% visual correctness. Comfort-fit rubber temples and nose pieces prevent eyewear from slipping while also providing maximum comfort. This model also features an indoor/outdoor PFT lens. Thanks to its chemical and physical properties, Performance Fog Technology is a permanent coating that prevents the formation of condensation on the lenses by absorbing the humidity drops.

BH9G - optional removable flame-resistant foam gasket available for all Dorado® safety glasses.

FEATURES

- PFT - Performance Fog Technology lens: Better than traditional anti-fog! This water-washable, hydrophilic anti-fog lens coating is permanently bonded to the lens to absorb moisture and evenly disperse it, providing clear, fog-free vision
- Wide-fit frame to fit a variety of face sizes
- Comfort-fit temples prevents slipping
- Dual 8 base curve lenses for full protection and visual correctness

TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses and frames constructed with the highest quality polycarbonate.

- Z87+ — MEETS ANSI/ISEA Z87.1-2020 STANDARDS
- ANSI/ISEA Z87.1-2020 ANTI-FOG — MEETS ANTI-FOG STANDARD
- ARC FLASH TESTED — ARC FLASH TESTED TO 35 CAL/CM²
- BALLISTIC RATED — MEETS MILITARY SPECS FOR BALLISTICS
- ERGONOMIC FIT — ERGONOMIC FIT RELIEVES PRESSURE
- HARD COAT — ANTI-SCRATCH HARD COAT TREATED LENS
- PERFORMANCE FOG TECHNOLOGY — PERMANENT HYDROPHILIC COATING
- TAPERED LENS — TAPERED LENS ELIMINATES DISTORTION
- UV PROTECTION — FILTERS 99.9% UVA/UVB/UVC LIGHT RAYS
- FLAME RESISTANT FOAM — PROVIDES SEAL AGAINST DEBRIS AND IMPACT *Optional

- Contemporary full frame for improved protection
- Soft, non-slip TPR nose piece
- Meets ANSI/ISEA Z87.1-2020 standards
- Meets ANSI/ISEA Z87.1-2020 anti-fog properties standard

SPECIFICATIONS

LENS	LIGHT TRANSMITTANCE	FRAME TYPE	FRAME COLOR	FRAME WIDTH	BASE CURVE	TEMPLE LENGTH	END OF TIPS WIDTH	WEIGHT
Indoor/Outdoor PFT	56%	Full Frame	Matte Black	140 mm	8	123 mm	94 mm	29 Grams

PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	810033297267	10810033297264	20810033297261

Arc Flash tested lens and frames to ASTM F2621/F2621M, which evaluates the lens response characteristics in an electrical arc exposure with a range up to approximately 25 Cal/cm². The frame retained its shape and did not distort or melt. An after-flame was not observed on the lens or frames.

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@BullheadSafety.com

BullheadSafety.com

Bullhead Safety®