

Sapphire™ Indigo™ Extreme Cut Resistant Touch Screen Gloves with Foam Nitrile Coating

Description

Maximum protection, lasting comfort, and reliable grip for high-risk industrial tasks. This glove delivers top-tier cut resistance with engineered yarns reinforced by metal fibers, offering superior safety when handling sharp, heavy parts. The nitrile foam palm coating ensures a strong grip in dry and oily environments, while a 13-gauge seamless Tuffalene® UHMWPE shell provides excellent cushioning and dexterity. Features include touch screen compatibility and a breathable back to reduce perspiration during extended use. The seamless knit and elasticized wrist enhance comfort and provide a secure fit, making this glove ideal for all-day wear in demanding industrial settings.



INDUSTRY	
Automotive	Highway Work
Construction	Machinery
Manufacturing	Plant Operation
Utilities	Product Assembly

Features

- 13-gauge Tuffalene® UHMWPE shell offers cushioning effect when handling heavy, sharp objects
- Foam nitrile provides excellent dry, wet, and oily grip with breathability
- Engineered yarns with metal fibers ensure the highest cut protection available on the market
- Touch screen compatible fingertips
- Designed for easy movement and continuous wear
- Breathable back of hand to reduce perspiration
- Seamless knit construction prevents irritation for the user
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use
- EN 388:2016 + A1:2018 Levels: 4X42F

Specifications

SHELL	SHELL COLOR	GAUGE	COATING	COATING COLOR	COATING TYPE	FINISH	TOUCH SCREEN	CUT
Tuffalene® UHMWPE	Blue	13-Gauge	Nitrile	Black	Palm	Foam	Yes	Level A9
ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS				
6,871 Grams	Level 6	Level 3	65 Newtons	4X42F				

Packaging

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
SKU		SKG00088DD	SKG00088DF	SKG00088DH	SKG00088DJ	SKG00088DL
INNER PACK UPC	12/PACK	810168163857	810168163864	810168163871	810168163888	810168164755
CASE GTIN	6 PK/CASE	10810168163854	10810168163861	10810168163878	10810168163885	10810168164752
OVERCAST COLOR		White	Green	Brown	Yellow	Gray

ITEM **SKG00088D** SIZES **7(S)-11(2XL)**



Meets ANSI/ISEA 105-2016 standard

- Cut Level A9
- ASTM F2992-15 Results = 6,871 grams
- Abrasion Level 6
- Puncture Level 3
- Puncture Results: 65 Newtons