

## Vise Gripster® C.I.A. High-Visibility Mach Finish Nitrile-Coated Gloves with Cut, Abrasion, Puncture, and Impact Resistance

### Description

These 13-gauge cut and impact resistant gloves feature a high-visibility yellow/green seamless Tuffalene® UHMWPE shell and high-visibility orange Mach Finish double nitrile-coated palm. The back of the hand and fingers have TPU impact protection to protect the metacarpal bones. A reinforced thumb crotch and padded palm add durability and help extend the life of the glove. The palm has an orange Mach Finish nitrile coating for enhanced grip. These gloves feature a knit wrist and a hook-and-loop closure for a comfortable, secure fit. Anti-static/electrostatic compliant for use in an ESD protected area.



INDUSTRY		
Oil and Gas	Utilities	Warehousing
Automotive	Construction	Agriculture
Petrochemical	Maintenance	

ITEM **CIA995MFV** SIZES **7(S)-11(2XL)**



### Features

- Tuffalene® UHMWPE shell is comfortable and dexterous
- Double-dipped Mach Finish nitrile offers excellent grip in wet and oily conditions and prevents liquids from saturating gloves
- Soft, flexible, TPU impact protection over the fingers and metacarpal bones provides tough protection
- Reinforced thumb crotch increases abrasion resistance in vulnerable area
- Padded palm provides added protection against vibration, punctures and impact

- Knit wrist with hook-and-loop closure allows users a secure and comfortable fit
- Anti-static/electrostatic compliant
- EN 388 Levels: 4X43E
- EN 407:2020: X2XXXX

### Meets ANSI/ISEA 105-2016 standard

- Cut Level A5
- ASTM F2992-15 Results = 2,385 grams
- Abrasion Level 4
- Puncture Level 4
- Puncture Results: 120 Newtons

### Meets ANSI/ISEA 138-2019 standard

- Impact Level (Overall): 2
- Impact Level (Knuckles): 2
- Impact Level (Fingers/Thumb): 2

### Specifications

SHELL	SHELL COLOR	GAUGE	COATING	COATING COLOR	FINISH	CUFF	IMPACT PROTECTION	
Tuffalene® UHMWPE	High-Visibility Yellow/Green	13-Gauge	Double Nitrile	High-Visibility Orange	Mach Finish	Knit Wrist with Hook-and-Loop	TPU	
CUT	ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	IMPACT	ANTI-STATIC/ELECTROSTATIC	EN 388 LEVELS	EN 407 LEVELS
Level A5	2,385 Grams	Level 4	Level 4	120 Newtons	Level 2	Compliant	4X43E	X2XXXX

### Packaging

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	N/A	N/A	N/A	N/A	N/A
INNER PACK UPC	12/PACK	816679011335	816679011366	816679011373	816679011380	816679011397
CASE GTIN	6 PK/CASE	10816679011332	10816679011363	10816679011370	10816679011387	10816679011394
CASE WEIGHT (IN POUNDS)		35	36.25	40	41	42.75



763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

13915 Radium St NW  
Ramsey, MN 55303