BULLHEAD SAFETY® HEARING PROTECTION

Corded Reusable Silicone NRR 26 dB Earplugs



DESCRIPTION

These triple-flange silicone earplugs provide effective protection against hearing damage by greatly reducing environmental noise. High-visibility and shaped to gently conform to the ear canal, the extra soft silicone is rated for a protection level of NRR 26 dB.

INDUSTRY

Airport Crews	Utility Work
Construction	Transportation
Automotive	Manufacturing
Printing	Waste Management

ITEM HP-S2 **NRR** 26 DB

REUSABLE EARPLUGS | CORDED | NRR 26 dB

FEATURES

- Cord helps prevent loss
- Environmentally friendly, 100% silicone
- Manufactured through vulcanization, not mold injected for ultimate flexibility
- Packaged: 1 pair per personal carrying case (includes belt attachment)
- Extra-soft, lightweight silicone seals the ear canal without pressure
- Triple-flange shape with firm handle provides an easy to insert, snug fit while gently conforming to the ear canal

SPECIFICATIONS

MATERIAL	SHAPE	COLOR	CORDED	METAL DETECTABLE	REUSABLE	PAIRS/BOX	EN 352-2: 2002 SNR RATING	ANSI S3. 19-1974 NRR RATING
Silicone, PVC Cord	Triple-Flange	High-Visibility Lemon	Yes	No	Yes	100	32 dB	26 dB

ANSI S3.19-1974 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
MEAN ATTENUATION (DB)	33.5	30.9	36.2	34.1	36.3	41.1	40.3	41.1	45.1	26 dB
STANDARD DEVIATION (DB)	5.3	5.4	4.9	4.7	2.8	4.1	4.7	5.0	2.4	

EN 352-2: 2002 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	125	250	500	1000	2000	4000	8000
SOUND ATTENUATION (DB)	34.5	30.4	36.0	31.9	36.4	41.2	43.0
STANDARD DEVIATION (DB)	5.8	4.4	4.7	4.6	4.8	5.6	4.1
ASSUMED PROTECTION (DB)	28.8	26.0	31.3	27.3	31.2	35.6	38.9
		SNR = 32 dB	H = 32 dB	M = 29 dB	L = 28 dB		

PACKAGING

	QUANTITY	HP-S2
INNER BOX	100PAIRS/PACK	10810292029613
CASE	10PK/CASE	20810292029610
CASE WEIGHT (IN POUNDS)		31.5

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@BullheadSafety.com

BullheadSafety.com