POMPANO™

BULLHEAD SAFETY® EYE PROTECTION

PFT PERFORMANCE FOG TECHNOLOGY

BH2763PFT

LENS Smoke Performance Fog Technology

FRAME Matte Black

DESCRIPTION

A lightweight, full-frame style, the Pompano™ is a good choice for many face shapes. The sleek design features embedded TPR nose pieces and temple ends to ensure a comfortable and secure fit. The BH2763PFT features a PFT lens. Thanks to its chemical and physical properties, Performance Fog Technology is a permanent coating that prevents the formation of condensation on the lenses by absorbing the humidity drops.

TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses and frames constructed with the highest quality polycarbonate.

FEATURES

- PFT - Performance Fog Technology lens: Better than traditional anti-fog! This water-washable, hydrophilic anti-fog lens coating is permanently bonded to the lens to absorb moisture and evenly disperse it, providing clear, fog-free vision
- Dual 8 base curve lenses for full protection and visual correctness
- Lightweight full-frame design
- TPR temple ends to prevent slipping
- Embedded TPR nose pieces to ensure eyewear stays put
- Meets ANSI/ISEA Z87.1-2020 standards
- Meets ANSI/ISEA Z87.1-2020 anti-fog properties standard

Z87+ — MEETS ANSI/ISEA Z87.1-2020 STANDARDS

ANSI/ISEA Z87.1-2020 ANTI-FOG — MEETS ANTI-FOG STANDARD

ARC FLASH TESTED — ARC FLASH TESTED TO 35 CAL/CM²

ERGONOMIC FIT — ERGONOMIC FIT RELIEVES PRESSURE

HARD COAT — ANTI-SCRATCH HARD COAT TREATED LENS

PERFORMANCE FOG TECHNOLOGY — PERMANENT HYDROPHILIC COATING

TAPERED LENS — TAPERED LENS ELIMINATES DISTORTION

UV PROTECTION — FILTERS 99.9% UVA/UVB/UVC LIGHT RAYS

SPECIFICATIONS

LENS	LIGHT TRANSMITTANCE	FRAME TYPE	FRAME COLOR	FRAME WIDTH	BASE CURVE	TEMPLE LENGTH	END OF TIPS WIDTH	WEIGHT
Smoke PFT	16%	Full Frame	Matte Black	137 mm	8	129 mm	92 mm	28 Grams

PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	810033297250	10810033297257	20810033297254

Arc Flash tested lens and frames to ASTM F2621/F2621M, which evaluates the lens response characteristics in an electrical arc exposure with a range up to approximately 25 Cal/cm². The frame retained its shape and did not distort or melt. An after-flame was not observed on the lens or frames.

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@BullheadSafety.com

BullheadSafety.com

Bullhead Safety®