

Cut and Hypodermic Needle Resistant Cowhide Leather Gloves with Alycore® and Aramid Fiber Reinforcements

Description

These driver's style gloves provide extreme cut resistance and hypodermic needle protection with an Alycore® reinforced palm. See the diagram for a detailed explanation of Alycore® areas. The gloves have a premium-grade white grain cowhide shell sewn with DuPont™ Kevlar® for added durability. The ergonomic keystone thumb improves comfort, and the open cuff allows easy donning and removal. Each pair is individually hang-tagged for retail sale.



INDUSTRY	
Recycling	Lumber Industry
Cable	Rebar Handling
Construction	Barbed Wire
Demolition	
Forestry	



ITEM **AC3200** SIZES **7(S)-11(2XL)**

Features

- Alycore® delivers unparalleled results with ultimate technology in the world of cut, puncture, and needle resistance while still remaining lightweight, flexible, breathable, and washable
- Premium-grade grain cowhide leather provides excellent wear resistance and durability
- Sewn with aramid fiber for added durability and cut and heat resistance
- Ergonomic keystone thumb improves durability, comfort, and dexterity while reducing hand fatigue



- Overcast color on hem for easy size identification
- Open cuff allows for easy donning and removal
- Sold by the pair
- EN 388 Levels: 3X13F
- EN 407:2020: X2XXXX

Meets ANSI/ISEA 105-2016 standard

- Cut level A9 palm, cut level A7 bottom of fingers and thumb
- ASTM F2992-15 Palm Results = >8000 grams
- Hypodermic needle puncture resistance levels: Level 5 (palm), Level 3 (bottom of fingers and thumb)

Specifications

SHELL	COLOR	PALM	THUMB	CUFF	CUT	NEEDLE	ASTM F2992-15 RESULTS	EN 388 LEVELS	EN 407 LEVELS
Grain Cowhide	White	Reinforced Alycore®	Keystone	Open	Level A9/A7	Level 5/3	>8000	3X13F	X2XXXX

Packaging

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	816368026794	816368026800	816368026817	816368026824	816368026831
INNER PACK GTIN	12/PACK	10816368026791	10816368026807	10816368026814	10816368026821	10816368026838
CASE GTIN	6 PK/CASE	20816368026798	20816368026804	20816368026811	20816368026828	20816368026835
CASE WEIGHT (IN POUNDS)		13.6	13.2	14.5	15.1	15.5
OVERCAST COLOR		Red	Green	Brown	Blue	Yellow

Needle resistance level based off third-party independent lab test results using the ASTM F2878-10 standard with 25-gauge needles.



763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com

13915 Radium St NW
Ramsey, MN 55303