R=5U6.5

Data sheet for RESU6.5





Product Specification (1/2)

2019.April

RESU_{6.5}

Electrical Characteristics	
Total Energy Capacity	6.5 kWh
Usable Energy Capacity ¹⁾	5.9 kWh
Battery Capacity	126 Ah
Voltage Range	42.0 to 58.8 V $_{DC}$
Nominal Voltage	51.8 V _{DC}
Max. Charge/Discharge Current	100A
Peak Current ²⁾	109.5A for 3 sec.
Max. Charge/Discharge Power ³⁾	4.2kW
Peak Power ²⁾	4.6kW for 3 sec.
Battery Pack Round-Trip Efficiency	>95% (under specific condition)
Communication Interface	CAN 2.0B
DC Disconnect	Circuit Breaker, Contactor, Fuse

Operating Conditions

Installation Location	Indoor / Outdoor (Stand / Wall-Mounted)
Operating Temperature	-10 to 45°C
Operating Temperature (Recommended)	15 to 30°C
Storage Temperature	-30 to 60°C : ~7 days -20 to 45°C : ~ 6 months
Humidity	5% to 95%
Altitude	Max. 2,000m
Cooling Strategy	Natural Convection

Certification

Safety	Cell	UL1642
	Battery Pack	CE / RCM / FCC / TUV (IEC 62619) / UL1973
Emissions		IEC61000-6-1, IEC61000-6-3
Hazardous Materials Classification		Class 9
Transportation		UN38.3
Ingress Rating		IP55

^{*} Test Conditions - Temperature 25°C, at the beginning of life

 $[\]fint % \fint % \fin$

¹⁾ Value for Battery Cell Only (Depth of Discharge 90%). Actual usable energy at the AC output may vary by condition, such as the inverter efficiency and temperature.

²⁾ Peak Current excludes repeated short duration (less than 3 sec.) of current pattern.

³⁾ LG Chem recommends 2.2kW for maximum battery lifetime.




Product Specification (2/2)

2019.April

Features

RESU6.5 battery pack designed for photovoltaic systems is easily adaptable energy storage solution. With RESU Plus, RESU3.3/6.5/10 can be "cross-connected" with each other.

- ※ RESU Plus is an expansion kit specially designed for 48V models. Number of expandable battery units: up to 2EA
 - ☐ Easy and Flexible installation
 - : Easy to wall mount or install on floor
 - : Wide range of inverters available
 - ☐ Proven Safety and 10 year warranty
 - ☐ Compact size and space saving





Mechanical Characteristics		
	Width	452 mm (17.8")
Dimensions	Height	656 mm (25.8")
	Depth	120 mm (4.7")
Weight		52 kg (114.6lbs)



