



Solar company!

Colour your **LIFE!**

BISOL Spectrum



Deep RED

Coloured Glass

BISOL Spectrum

With respect for our natural surroundings and the architectural legacy in mind, we are introducing exclusive **BISOL Spectrum** photovoltaic modules with coloured glass, whereby you no longer have to compromise aesthetics for efficiency when harnessing the endless power of the sun.

BISOL Spectrum modules were designed not only to conform, but also to refine the architectural traits of buildings and roofs of various types and styles. Available in a wide palette of colours, BISOL Spectrum PV modules can now really become an integral part of the building by either seamlessly blending into the historic character of the building in its natural setting, or by contributing to the manifestation of the building's modern design features. Their unique look allows discreet blending with the scenery, hence preserving the timeless beauty of diverse natural settings. Either way, BISOL Spectrum modules will undoubtedly add a timeless aesthetical value.

Advantages:



Made in EU



Available in
variety of colours



A perfect colour
match to your roof



On-roof or BIPV



PID free



Module presorting
for higher profitability



Excellent low light
performance



Double
insulation

RED glass is a good choice for most European roofs, where the panels will be almost invisible, especially if the building is under cultural heritage protection.



Deep Red






ORANGE glass matches the shades of Dutch buildings and brick roofs all around the world, and maintains the colour recognition of the environment.

Terracotta ORANGE


Coloured Glass

Electrical Specifications @ STC (AM1.5, 1,000 W/m², 25 °C)


					
		Deep Red	Forest Green	Terracotta Orange	Alabaster White
Module Type	BDO	320	300	280	220
Nominal Power	P_{MPP} [W]	320	300	280	220
Short Circuit Current	I_{SC} [A]	9.55	9.30	8.30	6.55
Open Circuit Voltage	V_{OC} [V]	41.5	41.1	43.2	40.9
MPP Current	I_{MPP} [A]	9.10	8.70	7.55	6.20
MPP Voltage	V_{MPP} [V]	35.2	34.5	37.1	35.5
Power Output Tolerance		±3 %			
Maximum Reverse Current		18 A			
Maximum System Voltage		1,500 V (Application Class A)			

Power classes vary depending on colour. I Efficiency at irradiation 200 W/m²: 99.3 % of STC efficiency or higher. I Power measurement tolerance: ±3 %.

I-V Curve



Effective Efficiency



Terracotta Orange

Alabaster WHITE

Coloured Glass

Thermal Specifications


Current Temperature Coefficient	α	+ 0.06 %/ °C
Voltage Temperature Coefficient	β	- 0.27 %/°C
Power Temperature Coefficient	γ	- 0.35 %/°C
NOCT		44 ± 2 °C
Temperature range		- 40 °C to + 85 °C

In compliance with:



Certificates available upon special request. Additional charges may apply.

WHITE glass is a great solution for easy blend in with large surface buildings. White colour versatility is not the only advantage, but it will keep buildings cooler.



Alabaster White





*GREEN glass goes well with the natural environment
and is the greenest solution for the planet.*


Forest GREEN

Coloured Glass

Colour Availability

Spectrum PV module	Frames, BIPV Flashings, Middle and End Clamps	Solar Glass
 Deep Red	 RAL 8017	RAL 8015
 Forest Green	 RAL 6009	RAL 6007
 Terracotta Orange	 RAL 8004	RAL 8023
 Alabaster White	 RAL 9016	RAL 9016


The actual colour shades may vary from the images shown. Colour inconsistencies in a module may appear due to the nature of this product.



Forest Green



On-Roof Solution



Detail of standard frame


Guarantees:



Product guarantee
15 years



Linear guarantee
85% output in 25th year



Roofs represent 20-25% of the total urban area and with photovoltaics, they present an opportunity for sustainable building designs.




Solar energy produces no pollution, has no environmental effects and is ecologically acceptable.

Mechanical Specifications

Length x Width x Thickness	BDO: 1,770 x 1,050 x 35 mm BSO: 1,813 mm x 1,075 mm x 25 mm
Weight	BDO: 20.5 kg / BSO: 21 kg
Solar Cells	120 Half-Cut mono c-Si / 166 mm x 166 mm
Junction Box / Connectors / IP	Three bypass diodes / MC4 compatible / IP 68
Cable Lenght	Default: 1,200 mm On demand (for portrait orientation): 300 mm
Frame	Standard frame (anodized AL with drainage holes and rigid anchored corners) or BIPV (Solirif®)
Frame Colour	Any RAL colour code, black or silver
Back Sheet Colour	Black
Glass	3.2 mm glass with anti-reflective coating / tempered / high-transparency / low-iron content
Packaging	BDO: 30 modules per pallet / stackable 3 pallets high BSO: 24 modules per pallet / stackable 2 pallets high
Impact resistance	Hailstone / Ø 25 mm / 83 km/h (51 mph)

Dimensions






BIPV removes any distinction between energy systems and building materials. It is aesthetic, multi-functional, eco-friendly, and signals a step into the future.


Roof-Integrated Solution

BISOL Spectrum PV modules are also available as a BIPV solution used in roof-integrated applications, that can be more cost effective simply because their composition and location replaces a number of conventional components. The overlapping of the specially framed BIPV modules produces an elegant PV array that completely replaces the conventional roofing. Maximum visual conformity and an unobtrusive appearance of the PV system are achieved by fully matching the colour of the end flashings, making it especially appealing to the eye. Coloured PV modules teamed up with building-integrated trim allow the PV system to fully blend in with even the most particular roof types, offering new possibilities of applying photovoltaic to most delicate historic and listed buildings in conservation areas.



Detail of special BIPV (Solrif®) frame

Dimensions



BISOL Spectrum module with BIPV frame





"Thanks to the BISOL Spectrum, we now have the possibility to please all our customer concerns. Some of them dislike solar panels because of their aesthetic appearance, while for the majority the return on investment (ROI) is of the highest importance. Now we have the solution that meets both needs – BISOL Spectrum!"

Zonnepanelen Volendam, the Netherlands

BISOL Group

Latkova vas 59a
3312 Prebold
SLOVENIA

T: +386 (0)3 703 22 50

F: +386 (0)3 703 22 63

E: info@bisol.si

BISOL Benelux

T: +32 (0)484 08 80 78

E: info@bisol.be

BISOL France

M: +33 (0)6 72 37 22 64

E: info@bisol.fr

BISOL UK

Capital Business Centre
Unit 11J, 22 Carlton Road
South Croydon, CR2 0BS
UNITED KINGDOM

T: +44 (0)208 916 2404

E: info@bisol.co.uk

BISOL Italy

Via Bonazzi, 5
40013 Castel Maggiore (BO)
ITALY

T: +39 051 705 697

E: italia@bisol.com

Dealer information

Tolerances of values are $\pm 5\%$. Unspecified product properties remain under full discretion of BISOL.

Additional terms & conditions apply. Please see Standard Limited Guarantee and General Terms and Conditions.

© BISOL Group d.o.o. October 2021. All rights reserved. All information presented in this document is subject to change without prior notice. All photographic images featured in this document are symbolic.