

Solis Three Phase Inverters

» S5-GR3P(5-10)K-LV



Efficient

- Max. efficiency 98.0%
- String current up to **16A**
- Wide voltage range and low startup voltage

Smart

- Supports export power control
- Supports RS485, WiFi, GPRS
- Scan to register on SolisCloud, supports remote upgrade and control

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Automatic voltage stabilization technology in weak grid conditions

Economic

- Compact design, simple installation and maintenance
- > 150% DC/AC ratio
- Supports high power modules for lower installation costs

Model: **220V:** S5-GR3P5K-LV S5-GR3P6K-LV S5-GR3P10K-LV

Datasheet

Model Name	S5-GR3P5K-LV	S5-GR3P6K-LV	S5-GR3P10K-LV		
Input DC					
Recommended max. PV power	7.5 kW	9 kW	15 kW		
Max. input voltage		1100 V			
Rated voltage		330 V			
Start-up voltage		180 V			
MPPT voltage range		160-500 V			
Max. input current	16 A / 16 A		32 A / 32 A		
Max. short circuit current	20 A / 20 A		40 A / 40 A		
MPPT number/Max. input strings number	2/2		2/4		
Output AC					
Rated output power	5 kW	6 kW	10 kW		
Max. apparent output power	5.5 kVA	6.6 kVA	11 kVA		
Max. output power	5.5 kW	6.6 kW	11 kW		
Rated grid voltage		3/(N)/PE, 208 V / 220 V / 240 V			
Rated grid frequency		50 Hz			
Rated grid output current	13.1 A	15.7 A	26.2 A		
Max. output current	14.4 A	16.7 A	28.8 A		
Power Factor		>0.99 (0.8 leading - 0.8 lagging)			
THDi		<2%			
Efficiency					
Max. efficiency		98.0%			
EU efficiency		97.5%			
Protection					
DC reverse-polarity protection		Yes			
Short circuit protection		Yes			
Output over current protection		Yes			
Surge protection		Yes			
Grid monitoring		Yes			
Anti-islanding protection		Yes			
Temperature protection		Yes			
Integrated AFCI (DC arc-fault circuit protection)		Yes ⁽¹⁾			
Integrated DC switch		Optional			
General Data					
Dimensions (W*H*D)		310*563*219 mm			
Weight	17.8 kg		20 kg		
Topology		Transformerless			
Self consumption (night)		<1 W			
Operating ambient temperature range		-25 ~ +60°C			
Relative humidity		0-100%			
Ingress protection		IP66			
Cooling concept	Natural convection	Intelligent redundant fan-cooling			
Max. operation altitude	4000 m				
Grid connection standard	G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530				
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4				
Features					
DC connection		MC4 connector			
AC connection		Quick connection plug			
Display		LCD			
Communication	RS485, Optional: Wi-Fi, GPRS				

(1) Activation required.