

Hybrid Single-Phase Energy Storage System

Power Module



Model	X1-H3.68K-S	X1-H4.6K-S	X1-H5K-S	X1-H6K-S
	Battery Input			
Battery Type	LFP			
Charge Voltage Range	390 - 550VDC			
Discharge Voltage Range	370 - 500VDC			
Battery Capacity	5 - 30kWh			
	PV Input			
Max.Input Power	7.36 kW	9.2 kW	10 kW	12 kW
Max.Input Voltage	600VDC			
MPPT Voltage Range	80 - 550VDC			
Start-Up Voltage	100VDC			
MPPT Voltage Range	80-550VDC			
Rated Input Voltage	360VDC			
Max.Input Current	16 / 16ADC			
Isc PV Array Short Circuit Current	20 / 20ADC			
Number Of MPPTs	2			
Number Of Strings per MPPT	1			
	AC Output (On-Grid)			
Rated Output Power	3.68 kW	4.6 kW	5 kW	6 kW
Max.Output Apparent Power	4 kVA	5 kVA	5.5 kVA	6.6 kVA
Max Units In Parallel ¹	3			
Rated Output Voltage	220/230/240 V			
Rated Frequency	50/60 Hz			
Power Factor	0.8 ind - 0.8 cap			
THDI (@Rated Power)	< 3%			
	AC Output (Off-Grid)			
Rated Output Power	3.68 kW	4.6 kW	5 kW	6 kW
Max.Output Apparent Power	4 kVA	5 kVA	5.5 kVA	6.6 kVA
Peak Output Apparent Power (Duration)	7.2 kVA (10s)	10 kVA (10s)	10 kVA (10s)	10 kVA (10s)
Max Units In Parallel ¹	1			
Rated Output Voltage	220 / 230 / 240 VAC			
Rated Frequency	50/60 Hz			
THDU (@Linear Load)	< 2%			
Switch Time	< 10 ms			
	AC Input			
Max.Input Apparent Power	7.2 kVA	10 kVA	10 kVA	10 kVA
	Protection			
Anti-Isolation Protection	Yes			
Over Current Protection	Yes			
AC Short-Circuit Protection	Yes			
Over Voltage Protection	Yes			
DC Surge Prevention	Type II			
AC Surge Prevention	Type III			
Over Temperature Protection	Yes			
PV Input Reverse Polarity Protection	Yes			
Battery Input Reverse Polarity Protection	Yes			
Insulation Impedance Detection	Yes			
Residual Current Detection	Yes			
	Efficiency			
Max.Efficiency	97.4%	97.5%	97.4%	97.6%
European Efficiency	96.5%	96.7%	96.7%	97.1%
	Connectivity			
Internet Connectivity	Wi-Fi, Bluetooth, Ethernet, 4G (Optional)			
	Other			
Weight	19 kg			
W × H × D Dimensions	670 × 335 × 150 mm			
Noise	≤ 30dB ²			
Mounting Options	Ground or Wall ³			
Operation Temperature	-25 ° C to 60°C ⁴			
Relative Humidity	0 to 100%			
Max Operating Altitude	Up to 4,000 m, Power Derates from 2,000 m			
Ingress Protection Rating	IP66			
Warranty	10 Years Limited ⁵			
	Compliance Information (More information available upon request)			
Grid Connection Certifications	VDE-AR-N 4105, DIN VDE V 0124-100 (VDE V 0124-100), CEI 0-21, G99/1-9, G99/NI, C10/C11, NTS 2021 V2.1, UNE 2170021, UNE 217002, RD647, AS/NZS 4777.2, EN 50549-1, EN 50549-10, Order no 208, DTIS-230206-BRL			
Safety	EN IEC 62109-1,EN IEC 62109-2, AS 60947.3			
EMC	EN IEC 61000-6-1, EN IEC 61000-6-3			

5. Refer to Anker SOLIX X1 Home Energy Storage System Warranty Policy for details.



Model	X1-B5-H
	Performance Specifications
Battery Energy ¹	5 kWh
Battery Type	Li-ion (LFP)
Battery Voltage Range	350 - 550 VDC
Maximum Charge / Discharge Power	3 kW
Maximum Charge / Discharge Current	7.6 A
	Other
W × H × D Dimensions (mm)	670 × 360 × 150
Weight	51 kg
Ingress Protection Rating	IP66
Operating Temperature	-20 ° C to 55 ° C
Maximum Operating Altitude	Up to 4,000 m, Power Derates from 2,000 m
Warranty	10 Years ²
	Compliance Information
Certifications	IEC 62619, IEC 62040-1, VDE-AR-E 2510-50, UN38.3

1 The maximum capacity of an expansion battery is 5kWh. The actual capacity may vary depending on environmental conditions, such as temperature, transportation methods, and storage conditions.
2 Refer to Anker SOLIX X1 Home Energy Storage System Warranty Policy for details.



Battery Module	× 1	× 2	× 3	× 4 ²	× 5 ²	× 6 ²
Energy Capacity	5 kWh	10 kWh	15 kWh	20 kWh	25 kWh	30 kWh
Weight*	73.5 kg	124.5 kg	175.5 kg	232 kg	283 kg	334 kg
W × H × D Dimensions (mm) ²	670 × 765 × 150	670 × 1,125 × 150	670 × 1,485 × 150	670 × 1,485 × 150	670 × 1,485 × 150	670 × 1,485 × 150
				670 × 482 × 150	670 × 842 × 150	670 × 1,202 × 150

1 Includes floor mounting base and top cover.
2 Two column installation.