
Accessory data sheet

Product description	**Profile seal, size A, NBR black**
Order number	**16 8114 000**

Illustration



Technical data

Temperature range	-60°C bis +250°C
Color	schwarz

Matching products

31 5234 300 000 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm²
31 5234 500 000 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm²
31 5235 300 000 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm²
31 5235 500 000 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm²
31 5236 300 510 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm², wired, LED
31 5236 500 510 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm², wired, LED
31 5237 300 520 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm², wired, LED
31 5237 500 520 - Female solenoid valve connector DIN EN 175301-803, low housing, IP 67, moulded cabel PUR 0,75 mm², wired, LED
43 1700 000 03 - Female connector (panel mount) DIN EN 175301-803, low housing, VDE, UL and ETS approval, cable outlet 6 - 8 mm (limit temperature value with seal 16-8088-000)
43 1700 002 03 - Female connector (panel mount) DIN EN 175301-803, low housing, VDE, UL and ETS approval, cable outlet 8 - 10 mm (limit temperature value with seal 16-8088-000)
43 1700 004 03 - Female connector (panel mount) DIN EN 175301-803, low housing, VDE, UL and ETS approval, metric thread M16, cable outlet 6 - 10 mm (limit temperature value with seal 16-8088-000)
43 1702 000 04 - Female connector (panel mount) DIN EN 175301-803, low housing, VDE, UL and ETS approval, cable outlet 6 - 8 mm (limit temperature value with seal 16-8088-000)
43 1702 002 04 - Female connector (panel mount) DIN EN 175301-803, low housing, VDE, UL and ETS approval, cable outlet 8 - 10 mm (limit temperature value with seal 16-8088-000)
43 1702 004 04 - Female connector (panel mount) DIN EN 175301-803, low housing, VDE, UL and ETS approval, metric thread M16, cable outlet 6 - 10 mm (limit temperature value with seal 16-8088-000)
43 1704 000 03 - Female connector (panel mount) DIN EN 175301-803, high housing, VDE and ETS approval, cable outlet 6 - 8 mm (limit temperature value with seal 16-8088-000)
43 1704 002 03 - Female connector (panel mount) DIN EN 175301-803, high housing, VDE and ETS approval, cable outlet 8 - 10 mm (limit temperature value with seal 16-8088-000)
43 1704 004 03 - Female connector (panel mount) DIN EN 175301-803, high housing, metric thread M16, VDE and ETS approval, cable outlet 6 - 10 mm (limit temperature value with seal 16-8088-000)
43 1704 006 03 - Female connector (panel mount) DIN EN 175301-803, high housing, metric thread M16, VDE and ETS approval, cable outlet 6 - 10 mm (limit temperature value with seal 16-8088-000)
43 1706 000 04 - Female connector (panel mount) DIN EN 175301-803, high housing, VDE and ETS approval, cable outlet 6 - 8 mm (limit temperature value with seal 16-8088-000)
43 1706 002 04 - Female connector (panel mount) DIN EN 175301-803, high housing, VDE and ETS approval, cable outlet 8 - 10 mm (limit temperature value with seal 16-8088-000)
43 1706 004 04 - Female connector (panel mount) DIN EN 175301-803, high housing, metric thread M16, VDE and ETS approval, cable outlet 6 - 10 mm (limit

Product description	**Profile seal, size A, NBR black**
Order number	**16 8114 000**

temperature value with seal 16-8088-000)
43 1708 011 00 - Female connector (panel mount) DIN EN 175301-803, high housing with 6.3 mm Fast-on crimp contacts, VDE and ETS approval, (limit temperature value with seal 16-8088-000)
43 1708 012 00 - Female connector (panel mount) DIN EN 175301-803, high housing with 6.3 mm Fast-on crimp contacts, VDE and ETS approval, (limit temperature value with seal 16-8088-000)
43 1708 013 00 - Female connector (panel mount) DIN EN 175301-803, high housing with 6.3 mm Fast-on crimp contacts, VDE and ETS approval, (limit temperature value with seal 16-8088-000)
43 1708 014 00 - Female connector (panel mount) DIN EN 175301-803, high housing with 6.3 mm Fast-on crimp contacts, VDE and ETS approval, (limit temperature value with seal 16-8088-000)
43 1708 015 00 - Female connector (panel mount) DIN EN 175301-803, high housing with 6.3 mm Fast-on crimp contacts, VDE and ETS approval, (limit temperature value with seal 16-8088-000)
43 1708 016 00 - Female connector (panel mount) DIN EN 175301-803, high housing with 6.3 mm Fast-on crimp contacts, VDE and ETS approval, (limit temperature value with seal 16-8088-000)
43 1708 017 00 - Female connector (panel mount) DIN EN 175301-803, high housing with 6.3 mm Fast-on crimp contacts, VDE and ETS approval, (limit temperature value with seal 16-8088-000)
43 1714 131 03 - Female connector (panel mount) DIN EN 175301-803, low housing, high-voltage protected, LED, VDE and ETS approval, cable outlet 6 - 8 mm
43 1714 132 03 - Female connector (panel mount) DIN EN 175301-803, low housing, high-voltage protected, LED, VDE and ETS approval, cable outlet 8 - 10 mm
43 1714 133 03 - Female connector (panel mount) DIN EN 175301-803, low housing, high-voltage protected, LED, VDE and ETS approval, cable outlet 6 - 8 mm
43 1714 134 03 - Female connector (panel mount) DIN EN 175301-803, low housing, high-voltage protected, LED, VDE and ETS approval, cable outlet 8 - 10 mm
43 1714 135 03 - Female connector (panel mount) DIN EN 175301-803, low housing, high-voltage protected, LED, VDE and ETS approval, cable outlet 6 - 8 mm
43 1714 136 03 - Female connector (panel mount) DIN EN 175301-803, low housing, high-voltage protected, LED, VDE and ETS approval, cable outlet 8 - 10 mm
43 1726 110 03 - Female connector (panel mount) DIN EN 175301-803, high housing, high-voltage protected, VDE and ETS approval, cable outlet 6 - 8 mm
43 1726 112 03 - Female connector (panel mount) DIN EN 175301-803, high housing, high-voltage protected, VDE and ETS approval, cable outlet 8 - 10 mm
43 1728 122 04 - Female connector (panel mount) DIN EN 175301-803, high housing, high-voltage protected, VDE and ETS approval, cable outlet 6 - 8 mm
43 1730 140 03 - Female connector (panel mount) DIN EN 175301-803, high housing, high-voltage protected, LED, VDE and ETS approval
43 1730 142 03 - Female connector (panel mount) DIN EN 175301-803, high housing, high-voltage protected, LED, VDE and ETS approval
43 1732 145 04 - Female connector (panel mount) DIN EN 175301-803, high housing, high-voltage protected, LED, VDE and ETS approval
43 1732 146 04 - Female connector (panel mount) DIN EN 175301-803, high housing, high-voltage protected, LED, VDE and ETS approval
43 1770 006 03 - Female connector (panel mount) with strain relief DIN EN 175301-803, low housing, cable outlet 6 - 8 mm (limit temperature value with seal 16-8088-000)
43 1772 006 04 - Female connector (panel mount) with strain relief DIN EN 175301-803, low housing, cable outlet 6 - 8 mm (limit temperature value with seal 16-8088-000)
99 5700 00 03 - Adaptor, high housing, female connector (panel mount) DIN EN 175301-803, M12
99 5702 00 04 - Adaptor, high housing, female connector (panel mount) DIN EN 175301-803, M12