Note: This datasheet may be out of date.
Please download the latest datasheet of GCM21BR71H273KA37# from the official website of Murata Manufacturing Co., Ltd.
http://www.murata.com/en-US/products/productdetail?partno=GCM21BR71H273KA37%23

GCM21BR71H273KA37#


"#" indicates a package specification code.

NRND | Power-train | AEC-Q200 | RoHS | REACH | 125 °C max. | Reflow OK | Flow OK

< List of part numbers with package codes >
GCM21BR71H273KA37L GCM21BR71H273KA37K

Appearance & Shape





References

Packaging	Specifications	Minimum Order Quantity
L	180Embossed Tape	3000
K	330Embossed Tape	10000

Mass (typ.)	
1 piece	17mg
φ180mm Reel	102g

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Note: This datasheet may be out of date.
Please download the latest datasheet of GCM21BR71H273KA37# from the official website of Murata Manufacturing Co., Ltd.
http://www.murata.com/en-US/products/productdetail?partno=GCM21BR71H273KA37%23

GCM21BR71H273KA37#

"#" indicates a package specification code.

Specifications

Length	2.0±0.15mm
Width	1.25±0.15mm
Thickness	1.25±0.15mm
Capacitance	27000pF ±10%
Distance between external terminals g	0.7mm min.
External terminal size e	0.2 to 0.7mm
Operating Temperature Range	-55°C to 125°C
Rated Voltage	50Vdc
Size code in inch(mm)	0805 (2012M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.