

TECHNICAL FILE
FS243.01
HARNESS SPIDER COMBO 1



FS243.01 FALL SAFE™ SPIDER COMBO 1

- The genuine X-treme™ Spider Arachnida wrap around design with its characteristic 4 arms, was developed to support the upper body perfectly with comfort and without interfering with the users normal movement.
- The chest D-ring complying with the EN361, if linked to the working rope or to an anchor point, increases the upright body position, permitting the user to lean back with full support on the back, avoiding unnecessary efforts on the abdominal area. This also makes it the perfect harness to delay some of the suspension trauma effects or to rescue a victim in a proper way, permitting several adjustments and configurations
- Ventral aluminum D-ring attachment point as EN813 for sit harness, rope access, divides evenly the user weight between the waist belt and the leg straps at suspended working position optimizing comfort and equilibrium.
- The newly designed ventral loop gives a better and safer organization when several karabiners are attached, avoiding the clash and friction between those.
- Separate loops for the SERRIO seat which will free up space at the ventral loop for other equipments
- 2 lateral aluminum D-rings attachments points for positioning as the EN358 with added parking position function to avoid undesired catching during work
- 3 gear loops

READY TO USE WITH



Protected Labels with INSPECTOR BY FALL SAFE™. It gives you an efficient way of recording and storing information on inspections.





FS243.01

FALL SAFE™ SPIDER COMBO 1

DETAILS

- ❶ Fall arrest D-ring
- ❷ Ventral Karabiner
- ❸ Ventral D-ring
- ❹ Loops for Serrio seat
- ❺ Kwik connect buckles
- ❻ Fall arrest dorsal D-ring
- ❼ IZY buckles
- ❽ Gear loops
- ❾ Fall Arrest Indicator
- ❿ Integrated chest ascender strap, optimizing the tension and positioning of the blocker.
- ⓫ Inspector by Fall Safe™ Ready

SPECIFICATIONS

- Standard: EN358 EN813 EN361 CE marked
- Size: S/M; L/XL; XXL
- Weight: 2,1kg

	A	B	C	D
S/M	80-120	75-115	45-75	145-180
L/XL	95-130	90-135	55-85	160-195
XXL	110-140	105-150	65-95	175-210
Universal	Universal from A to D			



INSPECTOR READY

