

# Marine & Industrial Nozzle

## Style 372-BC

- Corrosion resistant brass construction ideal for marine, offshore production rigs, industrial and other corrosive environments
- Meets the stringent performance requirements of the US Coast Guard
- Effectively produces a constant gallonage from straight stream to full fog
- Combines quality stream performance at various pressures with the simplicity of a fixed orifice
- Custom flow and pressure combinations are available on request, delivered with a calibrated flow disc installed
- Tough, durable design that is easy to operate
- Standard operating pressure at 100 psi (7 bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Ideal for AFFF applications and compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)



## Specification

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				GPM	LPM
372-BC	1-1/2"(38mm)	8.5"(216mm)	7.5(3.4kg)	60,95 or 125	230, 360 or 475

# Marine & Industrial Nozzle

## Unique Features On Peorwk Industrial Nozzles



Flow pattern detents  
facilitate positive positioning  
and smooth action

Laser-etched anodized  
label for excellent  
durability and visibility

Unique series number  
for easy identification

New and improved  
handle design

Stainless filter mesh  
prevents blockage  
caused by debris

Choice of 1-1/2"NH  
or 2-1/2" BIM inlet

Fixed moulded teeth  
or stainless steel  
spinning teeth

Constant flow  
regardless of  
pattern change

Flow rate etched on the  
baffle on request  
Can be field retrofitted  
to optional flows and pressures

### Style 372-BC

Ergonomic design pistol grip  
(available in various colours)

Heavy-duty chrome  
plated metal shutoff  
ball for smooth action  
and long life

