



PROFESSIONAL

FS800

ANCHOR SLING

The FALL SAFE® FS800 SLING it's an anchor sling made from 25 mm webbing polyester. It is constructed with load bearing stitches giving this device a minimum breaking load strength of 22 kN.

TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - N/A
INSPECTION	Yearly
TRACEABILITY	N/A S/N QR Code
STANDARDS	CE - EN795:2012-B
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Polyester webbing
CLASS	B
MAX STRENGTH	22 kN
MAX RATED LOAD	120kg
MAX USERS NO.	1
DIMENSIONS	0.50 m to 6 m
WEIGHT PER SIZE EAN PER SIZE	FS800-0.50M - 0.60kg - 5605423820454
	FS800-6M - 0.74kg - 5605423420180
	FS800-4M - 0.68kg - 5605423420227
	FS800-3M - 0.51kg - 5605423420159
	FS800-2M - 0.23kg - 5605423420036
	FS800-2.5M - 0.25kg - 5605423420135
	FS800-1M - 0.11kg - 5605423420029
	FS800-1.5M - 0.14kg - 5605423820799
	FS800-1.2M - 0.11kg - 5605423420142
	FS800-0.8M - 0.80kg - 5605423420173
	FS800-0.60M - 0.70kg - 5605423420197



PROFESSIONAL

FS800

ANCHOR SLING

O FALL SAFE® FS800 SLING é um estropo para ancoragem feito a partir de fita de poliéster de 25mm. É construído com costuras para suporte de cargas, dando a este dispositivo uma mínima carga de ruptura de 22 kN.

Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	N/A S/N QR Code
NORMAS	CE - EN795:2012-B
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Polyester webbing
CLASSE	B
FORÇA MÁX	22 kN
CARGA MÁXIMA	120kg
Nº MÁX UTILIZADORES	1
DIMENSÕES	0.50 m to 6 m
PESO POR TAMANHO EAN POR TAMANHO	FS800-0.50M - 0.60kg - 5605423820454
	FS800-6M - 0.74kg - 5605423420180
	FS800-4M - 0.68kg - 5605423420227
	FS800-3M - 0.51kg - 5605423420159
	FS800-2M - 0.23kg - 5605423420036
	FS800-2.5M - 0.25kg - 5605423420135
	FS800-1M - 0.11kg - 5605423420029
	FS800-1.5M - 0.14kg - 5605423820799
	FS800-1.2M - 0.11kg - 5605423420142
	FS800-0.8M - 0.80kg - 5605423420173
	FS800-0.60M - 0.70kg - 5605423420197