



PROFESSIONAL

FS930

FS930 SERIES - FALL ARREST BLOCKS - 2M

FS930 DYNE SERIES is a range of retractable fall arrest blocks made of polyamide, stainless steel and carbon steel with highly resistant Dyneema® webbing. This block has a length of 2 meters and is certified according to the EN360 standard. It comes equipped with an energy absorber and fall indicators as well as a swivel anchor on top connected to the connector for greater user mobility. Its design and internal mechanism minimize the act of braking the equipment to prevent it from braking when it is unintentional and this keeps the movement of users freer and more productive.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN360:2002
INTRASTAT	84798997

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Steel, carbon, Dyneema®, Aluminium, PA6
WEBBING TYPE	Dyneema®
FALL ARREST INDICATORS	Yes
CONNECTORS	Aluminium
ENERGY ABSORBER	Yes
SHARP EDGE TESTED	No
MAX USERS NO.	1
HOUSING	PA6 + Glass filled
CHASSIS	Stainless steel, carbon steel
LENGTH	2 m
WEIGHT PER SIZE EAN PER SIZE	FS930-TB - 1.88kg - 5605423470352
	FS930-ZZ - 1.51kg - 5605423807066
	FS930-TY - 1.20kg - 5605423808575
	FS930-TC-19 - 1.51kg - 5605423812473
	FS930-TC - 1.51kg - 5605423802269
	FS930-FC - 1.82kg - 5605423813258
	FS930-BC - 1.93kg - 5605423801057
	FS930-B - 1.30kg - 5605423802887



PROFESSIONAL

FS930

FS930 SERIES - FALL ARREST BLOCKS - 2M

FS930 DYNE SERIES é uma gama de blocos retráteis antiqueda fabricados em poliamida, aço inoxidável e aço carbono com fita Dyneema® de alta resistência. Este bloco tem um comprimento de 2 metros e é certificado pela norma EN360. Vem equipado com absorvedor de energia e indicadores de queda assim como uma âncora giratória no topo de ligação ao conector para maior mobilidade do utilizador. O seu design e mecanismo interno minimizam o ato de travagem do equipamento para evitar que trave quando não seja intencional e isto mantém o movimento dos utilizadores mais livres e produtivos.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N
NORMAS	CE - EN360:2002
INTRASTAT	84798997

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Steel, carbon, Dyneema®, Aluminium, PA6
TIPO DE FITA	Dyneema®
INDICADORES DE QUEDA	Yes
CONECTORES	Aluminium
ABSORBEDOR DE ENERGIA	Yes
TESTADO ARESTAS CORTANTES	No
Nº MÁX UTILIZADORES	1
INVÓLUCRO	PA6 + Glass filled
CHASSIS	Stainless steel, carbon steel
COMPRIMENTO	2 m
PESO POR TAMANHO EAN POR TAMANHO	FS930-TB - 1.88kg - 5605423470352
	FS930-ZZ - 1.51kg - 5605423807066
	FS930-TY - 1.20kg - 5605423808575
	FS930-TC-19 - 1.51kg - 5605423812473
	FS930-TC - 1.51kg - 5605423802269
	FS930-FC - 1.82kg - 5605423813258
	FS930-BC - 1.93kg - 5605423801057
	FS930-B - 1.30kg - 5605423802887