



PROFESSIONAL

FS240-1

FLASH VERTIX

FS240-1 FLASH VERTIX is a full body harness whose main objective was to provide a unique functionality for jobs where there is a need to climb stairs, namely and for example wind turbines. Its Zig-Zag stitching allows for less impact on the user's back in the event of a fall. It has an aluminum d-ring on the back (A - EN361) and four front loops, two on the chest and two on the ventral area (1/2 A + 1/2 A - EN361). It also has two loops on the legs (EN813). This harness has 8 adjustment points for a perfect fit and the location of the buckles allows it to be opened fully and easily dressed like a jacket. The harness is identified with RFID tag, S/N tag and QR code for easy tracking and control.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 100kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN358:1999 CE - EN361:2002 CE - EN813:2008
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium, steel
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	PA6, silicone
WEBBING TYPE	PES 45mm water-repellent
D-RINGS	ALU D-ring at back and sides, webbing loops at front
ANCHOR POINTS (A)	5
SHOULDER PADDING	Yes - Croc Smooth Padding 3.0
LUMBAR PADDING	Yes - Croc Smooth Padding 3.0
LEG PADDING	Yes
PADDING MATERIAL	TPU, EVA, PA, high visibility mesh and fabric PES
SEAT CONNECTION POINT	No
TOOL HOLDERS	5
TOOL HOLDERS MAX LOAD	15kg
ADJUSTMENT POINTS	8
BUCKLES	4 ALU IZY quick connect buckles; 2 aluminium spring buckles; 2 ST bar buckles
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	Yes
WEIGHT PER SIZE EAN PER SIZE	FS240-1-S/M - 2.90kg - 5605423571233 FS240-1-L/XL - 3.30kg - 5605423571240 FS240-1-XXL - 3.60kg - 5605423571257



PROFESSIONAL

FS240-1

FLASH VERTIX

FS240-1 FLASH VERTIX é um arnês de corpo inteiro cujo grande objetivo foi fornecer uma funcionalidade única para trabalhos onde exista necessidade de subir escadas, nomeadamente e por exemplo turbinas eólicas. A sua costura em Zig-Zag permite um menor impacto nas costas do utilizador em caso de queda. Tem um d-ring de alumínio nas costas (A - EN361) e quatro loops frontais, dois no peito e dois na zona ventral (1/2 A + 1/2 A - EN361). Possui ainda dois loops nas pernas (EN813). Este arnês tem 8 pontos de ajuste para uma adaptação perfeita e a localização das fivelas permite que seja aberto na totalidade e vestido facilmente como um casaco. O arnês está identificado com tag RFID, etiqueta S/N e código QR para fácil rastreabilidade e controlo.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 100kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN358:1999 CE - EN361:2002 CE - EN813:2008
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Aluminium, steel
COMPONENTES TÊXTEIS	Polyester
OUTROS MATERIAIS	PA6, silicone
TIPO DE FITA	PES 45mm water-repellent
D-RINGS	ALU D-ring at back and sides, webbing loops at front
PONTOS DE ANCORAGEM (A)	5
PADDING OMBROS	Yes - Croc Smooth Padding 3.0
PADDING LOMBAR	Yes - Croc Smooth Padding 3.0
PADDING PERNA	Yes
MATERIAL DO PADDING	TPU, EVA, PA, high visibility mesh and fabric PES
PONTO LIGAÇÃO DE CADEIRA	No
SUPORTE DE FERRAMENTAS	5
CAPACIDADE MÁX. DO SUPORTE DE FERRAMENTAS	15kg
PONTOS DE AJUSTE	8
FIVELAS	4 ALU IZY quick connect buckles; 2 aluminium spring buckles; 2 ST bar buckles
INDICADORES DE QUEDA	Yes
SUPORTE DE LONGES	Yes
PESO POR TAMANHO EAN POR TAMANHO	FS240-1-S/M - 2.90kg - 5605423571233 FS240-1-L/XL - 3.30kg - 5605423571240 FS240-1-XXL - 3.60kg - 5605423571257