



PROFESSIONAL

FS053K-AC

GRIPPA WP LANYARD

FS053K GRIPPA is a work positioning rope (EN358) with an aluminum Grippa length adjuster which has an ergonomic shape that makes it easy to hold and maneuver. FS053K is made with 11mm professional static rope and its ends are protected by a plastic sheath. The standard reference is sold with the FS33562 and FS820 connectors, although the user can purchase the rope with several other combinations of connectors (upon request).



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN358:2018
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PA, PES, Aluminium, Polimero
WEBBING TYPE	Tubular webbing protection - Polyester
ROPE TYPE	PA (core) + PES (cover) 11 mm (static)
DEVICE	ALU adjustable Grippa device
CONNECTORS	FS33562 ALU auto lock 25kN; FS820 ALU screw lock 25kN (other combinations on request)
MAX LENGTH	4M
ENERGY ABSORBER	No
SEAMS PROTECTOR	Yes
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN PER SIZE	FS053K-2M - 1.00kg - 5605423802313 FS053K-AC-2M - 1.50kg - 5605423259933 FS053K-AC-3M - 1.50kg - 5605423300369



PROFESSIONAL

FS053K-AC

GRIPPA WP LANYARD

FS053K GRIPPA é uma corda de posicionamento de trabalho (EN358) com um ajustador de comprimento em alumínio e com um formato ergonómico que facilita a sua pega e manobra chamado Grippa. FS053K é fabricado com corda estática profissional de 11mm e as suas extremidades são protegidas por uma bainha de plástico. A referência standard é vendida com os conectores FS33562 e FS820, apesar do utilizador poder adquirir a corda com várias outras combinações de conectores (sob consulta).



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN358:2018
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PA, PES, Aluminium, Polimero
TIPO DE FITA	Tubular webbing protection - Polyester
TIPO DE CORDA	PA (core) + PES (cover) 11 mm (static)
DISPOSITIVO	ALU adjustable Grippa device
CONECTORES	FS33562 ALU auto lock 25kN; FS820 ALU screw lock 25kN (other combinations on request)
COMPRIMENTO MÁX	4M
ABSORBEDOR DE ENERGIA	No
PROTETOR DE COSTURAS	Yes
TESTADO ARESTAS CORTANTES	No
PESO POR TAMANHO EAN POR TAMANHO	FS053K-2M - 1.00kg - 5605423802313 FS053K-AC-2M - 1.50kg - 5605423259933 FS053K-AC-3M - 1.50kg - 5605423300369