



PROFESSIONAL

FS630

PURE ANCHOR LINE

FS630 is an 11mm polyamide rope anchor line that can be combined with the FS33344, FS33300 and FS33381 descenders or with the FS333320 and FS33340 rope grabs, thus allowing great possibilities of use and operation.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 120kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN353-2:1992
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PA, PA6, PES, Aluminium
ROPE TYPE	PA (core) + PES (cover) static rope 11mm
CONNECTORS	FS820 ALU screw lock 25kN
MAX LENGTH	100 m
ENERGY ABSORBER	No
SEAMS PROTECTOR	Yes
SHARP EDGE TESTED	No

WEIGHT PER SIZE | EAN PER SIZE

FS630-2M - 0,20kg - 5605423320442
FS630-B-20M - 1,93kg -
FS630-L-20M - 2,30kg - 5605423802399
FS630-B-3M-1355 - 1,50kg - 5605423804782
FS630-80M - 2,80kg - 5605423667585
FS630-75M - 2,70kg - 5605423000641
FS630-65M - 2,50kg - 5605423320411
FS630-5M-1355 - 0,60kg - 5605423804164
FS630-5M - 0,60kg - 5605423320244
FS630-55-2M - 0,20kg -
FS630-50M - 2,18kg - 5605423320381
FS630-40M - 2,13kg - 5605423320336
FS630-3M-1355 - 0,30kg - 5605423808780
FS630-35M - 2,08kg - 5605423320374
FS630-30M - 2,03kg - 5605423320299
FS630-2M-103 - 0,20kg - 5605423812749
FS630-25M - 1,98kg - 5605423320282
FS630-20M-022 - 1,93kg -
FS630-20M - 1,93kg - 5605423320275
FS630-15M-022 - 1,88kg -
FS630-15M - 1,88kg - 5605423320268
FS630-1355-1.9M - 1,83kg - 5605423804065
FS630-10M-1355 - 1,83kg - 5605423804171
FS630-10M-103 - 1,83kg - 5605423810585
FS630-10M - 1,83kg - 5605423320251
FS630-100M - 6,50kg - 5605423320541
FS630-1.9M-1355 - 1,85kg - 5605423804188
FS630-1.20-1355 - 1,65kg - 5605423804195
FS630-B-120M - 3,20kg -
FS630-B-30M - 1,70kg - 5605423000979
FS630-B-40M - 2,60kg - 5605423814149
FS630-B-60M - 2,80kg - 5605423814637
FS630-C-120M - 3,20kg - 5605423813630
FS630-C-20M - 1,93kg - 5605423813647
FS630-C-30M - 2,03kg - 5605423813654
FS630-C-40M - 2,13kg - 5605423813661
FS630-C-60M - 2,60kg - 5605423813678



PROFESSIONAL

FS630

PURE ANCHOR LINE

FS630 é uma linha de ancoragem de corda de poliamida de 11mm que pode ser combinada com os descensores FS33344, FS33300 e FS33381 ou com as bloqueadores de corda FS333320 e FS33340, permitindo assim grandes possibilidades de uso e funcionamento.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 120kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN353-2:1992
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PA, PA6, PES, Aluminium
TIPO DE CORDA	PA (core) + PES (cover) static rope 11mm
CONECTORES	FS820 ALU screw lock 25kN
COMPRIMENTO MÁX	100 m
ABSORBEDOR DE ENERGIA	No
PROTETOR DE COSTURAS	Yes
TESTADO ARESTAS CORTANTES	No

PESO POR TAMANHO | EAN POR TAMANHO

FS630-2M - 0,20kg - 5605423320442
FS630-B-20M - 1,93kg -
FS630-L-20M - 2,30kg - 5605423802399
FS630-B-3M-1355 - 1,50kg - 5605423804782
FS630-80M - 2,80kg - 5605423667585
FS630-75M - 2,70kg - 5605423000641
FS630-65M - 2,50kg - 5605423320411
FS630-5M-1355 - 0,60kg - 5605423804164
FS630-5M - 0,60kg - 5605423320244
FS630-55-2M - 0,20kg -
FS630-50M - 2,18kg - 5605423320381
FS630-40M - 2,13kg - 5605423320336
FS630-3M-1355 - 0,30kg - 5605423808780
FS630-35M - 2,08kg - 5605423320374
FS630-30M - 2,03kg - 5605423320299
FS630-2M-103 - 0,20kg - 5605423812749
FS630-25M - 1,98kg - 5605423320282
FS630-20M-022 - 1,93kg -
FS630-20M - 1,93kg - 5605423320275
FS630-15M-022 - 1,88kg -
FS630-15M - 1,88kg - 5605423320268
FS630-1355-1.9M - 1,83kg - 5605423804065
FS630-10M-1355 - 1,83kg - 5605423804171
FS630-10M-103 - 1,83kg - 5605423810585
FS630-10M - 1,83kg - 5605423320251
FS630-100M - 6,50kg - 5605423320541
FS630-1.9M-1355 - 1,85kg - 5605423804188
FS630-1.20-1355 - 1,65kg - 5605423804195
FS630-B-120M - 3,20kg -
FS630-B-30M - 1,70kg - 5605423000979
FS630-B-40M - 2,60kg - 5605423814149
FS630-B-60M - 2,80kg - 5605423814637
FS630-C-120M - 3,20kg - 5605423813630
FS630-C-20M - 1,93kg - 5605423813647
FS630-C-30M - 2,03kg - 5605423813654
FS630-C-40M - 2,13kg - 5605423813661
FS630-C-60M - 2,60kg - 5605423813678