



FS803

FILUM - ANCHOR WIRE

The FALL SAFE® FS803 consists of an 8mm galvanized steel cable, whose ends are joined by a carabiner. Works as a temporary and portable fall arrest system.



TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - N/A
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN795:2012-B
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Galvanized steel cable and aluminium
CLASS	B
MAX STRENGTH	22kN
MAX RATED LOAD	120kg
MAX USERS NO.	1
DIMENSIONS	0.50 m to 4 m
WEIGHT PER SIZE EAN PER SIZE	FS803-0.5M - 0.25kg - 5605423420289 FS803-4M - 2.00kg - 5605423420234 FS803-3M - 1.74kg - 5605423420241 FS803-2M - 1.16kg - 5605423420258 FS803-2.4M - 0.12kg - 5605423801552 FS803-1M - 0.58kg - 5605423470345 FS803-1.5M - 0.75kg - 5605423420272



FS803

FILUM - ANCHOR WIRE

O FALL SAFE® FS803 é constituído por um cabo de aço galvanizado de 8mm, em que as suas extremidades são unidas por um mosquetão. Funciona como sistema ant queda temporário e portátil.



Informação Técnica

TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N
NORMAS	CE - EN795:2012-B
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Galvanized steel cable and aluminium
CLASSE	B
FORÇA MÁX	22kN
CARGA MÁXIMA	120kg
Nº MÁX UTILIZADORES	1
DIMENSÕES	0.50 m to 4 m
PESO POR TAMANHO EAN POR TAMANHO	FS803-0.5M - 0.25kg - 5605423420289 FS803-4M - 2.00kg - 5605423420234 FS803-3M - 1.74kg - 5605423420241 FS803-2M - 1.16kg - 5605423420258 FS803-2.4M - 0.12kg - 5605423801552 FS803-1M - 0.58kg - 5605423470345 FS803-1.5M - 0.75kg - 5605423420272