



PROFESSIONAL

FS900RA

PULL SAFE - RESCUE EQUIPMENT

The FALL SAFE® FS900RA - PULLSAFE RESCUE EQUIPMENT is a manual lift rescue system with a DSD Plus descender device up to 2 persons. It is designed to perform secured lifts and controlled descends of victims: it has an integrated lightweight winch system with a 4:1 ratio that allows for a lift with much less effort and a DSD Plus Descender suitable for 2 persons with a specially designed handle to easily control the descend.

The FS900RA rescue kit includes 3 aluminium hooks with auto lock, 1 DSD Plus descender, 1 winch system and 1 storage bag.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 04/12/2018
INSPECTION	N/A
TRACEABILITY	N/A
STANDARDS	CE - EN341:2011-2A CE - EN12841:2006C
INTRASTAT	84799070

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium, Steel
TEXTILE PARTS	Polyester, PA
OTHER COMPONENTS MATERIAL	Silicone, Polimero, Heat shrink sleeve
ROPE TYPE	PA (core) + PES (cover) static rope 11 mm; PA (core) + PES (cover) static rope 9 mm
DEVICE	Winch System with 4:1 ratio FS33300 DSD PLUS descender (2 users)
CONNECTORS	FS821 ALU auto lock 23kN; FS33562 ALU auto-lock 25kN; FS33561 ST screw lock 28kN; FS802QL ST screw lock 25kN
MAX USERS NO.	2
COMPONENTS	Includes FS8214 carrying bag
WEIGHT PER SIZE EAN PER SIZE	FS900RA-20M - 4.55kg - 5605423430370 FS900RA-10M - 2.85kg - 5605423821062 FS900RA-120M - 17.00kg - FS900RA-30M - 0.68kg - 5605423430332 FS900RA-40M - 11.00kg - 5605423430363 FS900RA-60M - 16.50kg - 5605423753738



PROFESSIONAL

FS900RA

PULL SAFE - RESCUE EQUIPMENT

O FALL SAFE® FS900RA - PULLSAFE RESCUE EQUIPMENT é um sistema de resgate de elevação manual com um descensor DSD Plus para até 2 pessoas. Este sistema foi projetado para realizar elevações seguras e descidas controladas de resgate: possui um sistema de guincho leve integrado com rácio de 4:1 que permite elevar a vítima com muito menos esforço e um Descensor DSD Plus adequado para 2 pessoas com uma pega especialmente desenhada para controlar facilmente a descida.

O kit de resgate FS900RA inclui 3 ganchos de alumínio com fecho automático, 1 descensor DSD Plus, 1 sistema de guincho e 1 bolsa de armazenamento.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 04/12/2018
INSPEÇÃO	N/A
RASTREABILIDADE	N/A
NORMAS	CE - EN341:2011-2A CE - EN12841:2006C
INTRASTAT	84799070

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Aluminium, Steel
COMPONENTES TÊXTEIS	Polyester, PA
OUTROS MATERIAIS	Silicone, Polimero, Heat shrink sleeve
TIPO DE CORDA	PA (core) + PES (cover) static rope 11 mm; PA (core) + PES (cover) static rope 9 mm
DISPOSITIVO	Winch System with 4:1 ratio FS33300 DSD PLUS descender (2 users)
CONECTORES	FS821 ALU auto lock 23kN; FS33562 ALU auto-lock 25kN; FS33561 ST screw lock 28kN; FS802QL ST screw lock 25kN
Nº MÁX UTILIZADORES	2
COMPONENTES	Includes FS8214 carrying bag
PESO POR TAMANHO EAN POR TAMANHO	FS900RA-20M - 4.55kg - 5605423430370 FS900RA-10M - 2.85kg - 5605423821062 FS900RA-120M - 17.00kg - FS900RA-30M - 0.68kg - 5605423430332 FS900RA-40M - 11.00kg - 5605423430363 FS900RA-60M - 16.50kg - 5605423753738